

**TEC<sup>®</sup>**  
**Magnetostrictive**  
**Displacement Sensor**  
**R Series Product manual**



· High quality · High precision · Long service life

浙达精益——科技先行 以人为本

ZHEDAJINGYI

TECHNOLOGY FIRST PEOPLE-ORIENTED



中国创造·创造中国






















# CONTENT

---



TEC Product List	01
Company Profile	03
Honorary & Qualification	04
TEC Magnetostriction Development	05
RH/RP Series Displacement Sensors	10
Analog Output	10
SSI Output	17
Profibus-DP Output	24
CAN Bus Output	32
Profinet Output	40
Start-Stop Output	46
EtherCAT Output	53
RF Flexible Outer Tube Displacement Sensor	58
RD Split Displacement Sensor	72
RS Waterproof Displacement Sensor	86
RB Flat Displacement Sensor	95
FBGB Explosion-proof Displacement Sensor	102
Programming Tools Selection	116
Magnet ring Selection	117
Connector Selection	122
Cable Selection	125
Troubleshooting Table	127
Industrial Application	129

# TEC Product List











Appearance interface	 RH	 RP	 RS	 RF
Analog Current	0~20mA (or reverse) 4~20mA (or reverse)	0~20mA (or reverse) 4~20mA (or reverse)	0~20mA (or reverse) 4~20mA (or reverse)	0~20mA (or reverse) 4~20mA (or reverse)
Analog voltage	0~10V (or reverse) 0~5V (or reverse) -10~10V (or reverse) -5~5V (or reverse)	0~10V (or reverse) 0~5V (or reverse) -10~10V (or reverse) -5~5V (or reverse)	0~10V (or reverse) 0~5V (or reverse) -10~10V (or reverse) -5~5V (or reverse)	0~10V (or reverse) 0~5V (or reverse) -10~10V (or reverse) -5~5V (or reverse)
SSI	24/25/26bit/Gray code/ Binary	24/25/26bit/Gray code/ Binary	24/25/26bit/Gray code/ Binary	24/25/26bit/Gray code/ Binary
Profibus-DP				
PROFINET				
CANopen				
Start/Stop				
EtherCAT				

## CHARACTERISTICS

installation form	internal	external	internal	
measuring range	25~5500mm	25~5500mm	25~5500mm	500~23000mm
Protection level	IP67	IP65	IP68	IP65
magnet	various ring magnets	Slider magnet/Square magnet/Sector magnet	various ring magnets	various ring magnets
LED Diagnosis	✓	✓	-	✓
Diagnosis Software	✓	✓	✓	✓
Outer tube pressure	35MPa	-	35MPa	-
Outgoing mode	Cable outlet or Connector	Cable outlet or Connector	Cable outlet	Cable outlet or Connector



# TEC Product List


Appearance interface	 RB	 FBGB	 RD
Analog Current	0~20mA (or reverse) 4~20mA (or reverse)	0~20mA (or reverse) 4~20mA (or reverse)	0~20mA (or reverse) 4~20mA (or reverse)
Analog voltage	0~10V (or reverse) 0~5V (or reverse)	0~10V (or reverse) 0~5V (or reverse) -10~10V (or reverse) -5~5V (or reverse)	0~10V (or reverse) 0~5V (or reverse) -10~10V (or reverse) -5~5V (or reverse)
SSI	24/25/26bit/Gray code/ Binary	24/25/26bit/Gray code/ Binary	24/25/26bit/Gray code/ Binary
Profibus-DP			
PROFINET			
CANopen			
Start/Stop			
EtherCAT			

## CHARACTERISTICS

installation form	internal	internal	internal
measuring range	25~5500mm	25~5500mm	25~5500mm
Protection level	IP67	IP67	IP68
magnet	various ring magnets	various ring magnets	various ring magnets
LED Diagnosis	-	-	✓
Diagnosis Software	✓	✓	✓
Outer tube pressure	35MPa	35MPa	35MPa
Outgoing mode	Cable outlet or Connector	Cable outlet	Cable outlet or Connector

## Company Profile

We are a technological innovation enterprise born out of Zhejiang University. It is a national high-tech enterprise, the fourth batch of "small giant" enterprises of the Ministry of Industry and Information Technology, and a special enterprise of Zhejiang Province. Our company has more than 180 employees, including 4 overseas talents, 4 professors, and 2 associate professors. There are also 12 doctors, and more than 86% of employees with a bachelor degree or above.



We are committed to intelligent manufacturing, high-end equipment, intelligent sensing, intelligent detection, military industry and other fields. Most of our company's products are independently researched and developed, and the market share ranks in the forefront of the domestic industry. A variety of equipment is the first set in China, which breaks the long-term monopoly of foreign companies.

We are a national high-tech enterprise integrating scientific research, product development, engineering design, and technical consulting. Besides, the company has obtained 45 invention patents, 29 utility model patents, 10 software copyrights, and 4 registered trademarks.


Taking "Created in China, Create China" as our ideal, we are committed to building a century-old national brand. Our development goal is to become a well-known leading technology and strength-based enterprise in China's high-end equipment and intelligent inspection industries.



# Honorary Qualification



# TEC Magnetostriction Development



National Natural Science Foundation of China, "Research on Theory and Practice of Real-time Quantitative Detection of Defects in High-temperature Metal Pipelines Based on Magnetostrictive Guided Waves"

**IN 2013**

**IN 2016**

National Major Scientific Instrument and Equipment Development Project, "R&D of Rail Broken Monitoring Equipment and Testing Network in Key Sections"

National Key R&D Program, "On-line Monitoring and Inspection of Pressure Equipment and Dynamic Risk Management Technology Research"; Zhejiang Province Key R&D Program, "Usonic Guided Wave-based Track Turnout Structural Health Monitoring System"

**IN 2017**

**IN 2018**

National Natural Science Foundation of China, "Research on the Theory and Practice of On-line Monitoring of Turnout Point Rail Defects Based on Phased Array Guided Wave Sound Field Control"; National Key R&D Project, "Research on Magnetoacoustic Compound Monitoring and Detection Technology for Typical Pressure-bearing Special Equipment Damage"

Key R&D Program of Zhejiang Province, "Research and Demonstration Application of Safety Early Warning Technology for Nearshore High Tower Equipment"

**IN 2019**

**IN 2021**

Science and Technology Progress Award of Zhejiang Province, "High-precision magnetoacoustic sensing technology and industrialization application of important components".


**IN 2022**

The fourth batch of "Small Giant" enterprises of the Ministry of Industry and Information Technology of the People's Republic of China, and the specialized and special new enterprises of Zhejiang Province



## Quality Assurance

After years of experience and precipitation, TEC magnetostrictive displacement sensor has built a modern, automatic and standardized production line, which ensures the reliability, stability and consistency of products. Before the new series of products are put into the market, they must pass EMC, vibration, impact, high and low temperature tests. Sensors need to go through signal verification before and after each manufacturing process. After assembly, they are tested and screened one by one. Finally, they pass the calibration and linearity detection of laser interferometer, and the detection results are uploaded to the database for subsequent tracking of products



Laser interferometer: Calibrated by laser interferometer can measure up to 1000 points per millimeter

## Parts Test

### Electro Magnetic Compatibility (EMC)

Electrostatic discharge immunity	( GB/T17626.2, IDT IEC61000-4-2 )
Radiation immunity of radio frequency electromagnetic field	( GB/T17626.3, IDT IEC61000-4-3 )
Immunity of electrical fast transient	( GB/T17626.4, IDT IEC61000-4-4 )
Surge (shock) immunity	( GB/T17626.5, IDT IEC61000-4-5 )
RF field induced conducted disturbance immunity	( GB/T17626.6, IDT IEC61000-4-6 )
Power frequency magnetic field immunity	( GB/T17626.8, IDT IEC61000-4-8 )

### Temperature Test

Low temperature	( GB/T2423.1, IDT IEC60068-2-1 )
High temperature	( GB/T2423.2, IDT IEC60068-2-2 )
Constant damp heat	( GB/T2423.3, IDT IEC60068-2-78 )
Alternating damp heat	( GB/T2423.4, IDT IEC60068-2-30 )
Temperature change	( GB/T2423.22, IDT IEC60068-2-14 )

### Other Tests

Explosion-proof test	( GB3836.1, IDT IEC60079-0 )
Explosion-proof test	( GB3836.2, IDT IEC60079-1 )
Explosion-proof test	( GB3836.4, IDT IEC60079-11 )
Insulation resistance, insulation strength	( GB/T15479 )
Impact test	( GB/T2423.5, IDT IEC68-2-27 )
Free drop test	( GB/T2423.8, IDT IEC68-2-32 )
Vibration test	( GB/T2423.10, IDT IEC68-2-6 )
Highly accelerated life test	( HALT )
Enclosure protection test	( GB/T4208-2017 )

# Technical Terminology

## ● Absolute position

The output of the sensor is relative to a fixed reference point, which does not need to be reset when power supply is restored after power failure; this position is an absolute position. However the general incremental sensor, such as incremental encoder and incremental grating ruler, which needs to find the reference point again.

## ● Environmental conditions

For normal Operating conditions of displacement sensors, the industry has the following standards:

a ) Temperature:  $25^{\circ}\text{C}$  ( $\pm 10^{\circ}\text{C}$ )

b ) Relative humidity: 90% or less

Generally, the environment for calibrating and testing sensors is more stringent than the standard requirements.

## ● Measuring range

For the sensor, the physical quantity to be measured is indicated by upper and lower limits. The measurement range is the full scale of motion.

## ● Full scale

Full scale (abbreviated as "F.S") (see measuring range).

## ● Resolution

Refers to the minimum amount of sensor output that can be distinguished. The highest resolution of TEC magnetostrictive displacement sensor can reach  $1\mu\text{m}$ .

## ● Nonlinearity

Nonlinearity is the absolute deviation as a percentage of the Stroke length. In a magnetostrictive sensor, this change is caused by the difference in the propagation velocity of the return signal propagating in the waveguide medium.

## ● Non-contact

Magnetostrictive displacement sensor uses non-contact magnetic induction technology to measure position. Non-contact measurement does not exist mechanical wear and mechanical vibration, which improves the reliability and service life of the sensor.

## ● Temperature coefficient

The temperature coefficient unit is  $\text{ppm}/^{\circ}\text{C}$  (one millionth per degree Celsius). It refers that the ambient temperature changes by 1 degree Celsius, the amount of change in the position value output by the sensor.

## ● Update time

The time interval between two measurements made by the sensor. The larger the range of the sensor, the longer the update time required.

## ● Multiple position measurement

Measure the position of multiple magnet rings on the sensor stroke shaft or guide rail at the same time.

## ● Precision

The difference between the indicated measured value and the true value can be calculated from the root mean square of the nonlinear deviation, repeatability, and hysteresis.

## ● Hysteresis

The difference in displayed position when reaching the same point from opposite directions along the length of stroke (Note: Magnetostrictive displacement sensors have very little hysteresis and are therefore negligible in most applications).

## ● Drift

Drift refers to the change of output signal or output value under the influence of surrounding environment, such as time or temperature. Please refer to "preheating period" and "temperature coefficient" at the same time.

## ● Shell protection class

The IP (Ingress Protection) standard for shell intrusion protection issued by the International Electrotechnical Commission. For specific IP standard instructions, please refer to the official website of IEC. The optional protection levels of sensors are IP65, IP67 and IP68.

## ● Preheating period

The time required for the sensor to be energized until the output is stable, this deviation can be seen from the calibration curve of the sensor.

## ● Load impedance

The impedance when the external circuit is connected to the output end of the sensor.

## ● Repetition accuracy

The difference in sensor output when the magnet repeatedly reaches the same position from the same direction when measured along the stroke.

# Technical Characteristics

## CC Product Introduction

TEC magnetostrictive displacement sensor is a new generation of linear displacement sensor independently developed by Zheda Jingyi. It can provide users with real-time, reliable, accurate and continuous linear displacement signals under harsh working environment, and is widely used in metallurgical equipment, wind power equipment, construction machinery, rubber machinery, port machinery, energy and other industrial automation fields.

## CC Product Characteristics

### High precision

The highest resolution and repetition accuracy can reach  $0.1\mu\text{m}$

### Extra long stroke

Up to 23 meters

### Never wear

Non-contact measurement, maintenance-free and calibration-free, and the detection accuracy is always as new.

### Various signal output forms

Analog (voltage, current), SSI, Start/Stop, Profibus-DP, CANopen, Profinet, EtherCAT

### Strong adaptability

It can work in harsh environment such as high and low temperature, humidity, vibration, impact, corrosion, dust and so on. It can work in harsh environment such as high and low temperature, humidity, vibration, impact, corrosion, dust and so on.

### Strong shell

The 304 stainless steel tube shell is precision welded, with pressure resistance, dust resistance, pollution resistance, and electrical protection grades up to IP65, IP67, and IP68.

### Easy to use


M18 $\times$ 1.5、M20 $\times$ 1.5、3/4"-16UNF-3A threaded installation is optional. When replacing the sensor, only the electronic compartment can be replaced without removing the pressure measuring rod.

### Reliable operation

The core components have been tested for durability, impact, vibration, temperature and absolute displacement, and are not affected by power failure.

## Gg Working Principle

The detection mechanism of the magnetostrictive displacement sensor is based on the "Weidmann effect" between the magnetostrictive waveguide wire and the vernier magnet which is the core detection element of the sensor. The excitation module in the sensor electronic bin will apply a query pulse at both ends of the loop where the sensitive detection element (magnetostrictive waveguide wire) is located, and the pulse forms a circumferential ampere annular magnetic field around the waveguide wire at speed of light. The magnetic field is coupled with the permanent magnet magnetic field at the position of the vernier magnet, and a "Weidmann effect" torsional stress wave is formed on the surface of the waveguide wire. The torsional wave transmitted to the end is absorbed by the damping device, and the signal transmitted to the excitation end is received by the detection device. The control module calculates the time difference between the inquiry pulse and the received signal, and multiplies it by the propagation speed of torsional stress wave in the waveguide material, so as to calculate the distance between the torsional wave occurrence position and the measurement reference point, and realize the real-time accurate measurement of the vernier magnet position.



Working principle of magnetostrictive linear displacement sensor



# RH/RP Displacement Sensor- Analog Output



## Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Easy to use, standard analog signal output
- No need to return to zero, absolute position output
- Easy diagnosis, LED real-time condition monitoring
- Low power consumption design effectively reduces system heating
- Stable and reliable, using digital analog technology
- The start and end position of the measurement can be adjusted in full scale

## C Product Parameters-Analog Output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500 mm, customized according to customer needs
Number of measurements	1

### • Output

Current	4 ~ 20mA or 20 ~ 4mA(min/max load 0/5002)
Voltage	0 ~ 10Vdc or 0~5Vdc (min load resistance ≥ 10K)
Resolution	16-bit D/A or 0.0015% of full scale (min 1um)
Nonlinearity	<±0.01% of full scale, min±50um
Repetition accuracy	<±0.001% of full scale, min ±1um
Hysteresis	< 10um
Update time	1KHz (range ≤ 1m), 500Hz (1m < range ≤ 2m), 333Hz (2m < range ≤ 3m), customizable
Temperature coefficient	<30ppm/°C

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67 RH Stainless Stell Rod /IP65 RP Aluminum profile
Operating temperature	-40°C ~ +85°C
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Structure and Materials


	Failure indication	Displayed by the LEDs on the rear cover of the electronic compartment
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa (continuous) /70MPa (peak) or 350bar (continuous) / 700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
	Mounting thread form	M18×1.5、M20×1.5、3/4"-16UNF-3A (customizable)
	Installation direction	Any direction
	Outgoing mode	Cable outlet or Connector

### • Electrical Connections

Input voltage	+24Vdc±20%
Operating current	<80mA (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	> 10MΩ
Insulation strength	500V

## S Output Characteristics-Analog Output

- The measurement accuracy of analog output magnetostrictive displacement sensor depends on the number of bits of built-in D/A module. Displacement signals can be directly output to external controllers, such as analog input of PLC.
- The sensor transforms the absolute position of the vernier magnet into a standard analog signal in real time, that is, 0~20A (or reverse), 4~20mA (or reverse) DC current or 0~5V (or reverse), -5~+5V (or reverse), 0~10V (or reverse), -10~+10 (or reverse) DC voltage, etc. The change trend of the output value is linear with the movement direction of the magnet ring, which can be set as forward and reverse output according to needs. As shown in the following figure:




Current output includes: 0~20mA (or reverse) 、 4~20mA (or reverse)

Voltage output includes: 0~5V (or reverse) 、  
-5~+5V (or reverse) 、 0~10V (or reverse) 、  
-10~+10V (or reverse)

## L LED Real-time State Monitoring and Diagnosis

- Red and green LED indicator built into the sensor head cover provide sensor working condition and diagnostic function.

Green light	ON	ON	ON	Flash
Red light	OFF	Flash	ON	ON
Function	Normal work	Magnet leaves Stroke length range	Magnet not detected	Programming status



## B Programming

- TEC sensors are field programmable using a USB converter. No need to open the electronic bin, USB port power supply, standard cable connection, fully meet customer needs. The following parameters of the sensor can be modified through the configuration software on the PC side: set the measurement direction of the sensor; set the zero point and full scale point of the sensor; graphically display the magnet ring position value; diagnose the sensor online through the error code.



USB converter  
(Order No. TEC612811)



Sensor programming window


## A a Installation Instructions-Analog Output

Analog output magnetostrictive displacement sensor, suitable for real-time and precise measurement of moving parts stroke, it can measure the absolute displacement or stroke of vernier magnet, expressed in the form of standard analog quantity, including: 0~20MA (or reverse), 420MA (or reverse) DC current or 0~5V (or reverse), -5~+5V (or reverse), 0~10V (or reverse), -10~+10V (or reverse) DC voltage, etc. Sensors have built-in and external two different installation methods, built-in type is suitable for the built-in installation of hydraulic cylinders, compact structure; the external type adopts aluminum profile, which is installed outside the moving parts and convenient to use.

### • Dimensions and installation guidance of RH pressure-resistant rod sensor


RH series pressure-resistant rodshell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode. Mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The default values of the first and last measurement Non-usable areas of this product are 50.8mm and 63.5mm respectively. The value of the measurement Non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.



### • Dimensions and installation guidance of RP aluminum profile sensor

RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.



## C Common Accessories - Analog Output

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard magnet ring Order No.: 211501		Magnetic isolation gasket		6-pin Female Connector Order No.: 312701	
Sector magnet Order No.: 211502		Sector magnetic isolation gasket		6-pin 90 Female Connector Order No.: 312702	
Slider magnet Order No.: 211503		Square magnet Order No.: 211508			

**Note:** Please refer to "Magnet ring Selection" for details of magnet ring kit and other models.

### • Wiring mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet output, refer to the line color definition in the following table for connection mode



• 6-pin male connector arrangement (facing the sensor head)				• 8-pin male connector arrangement (facing the sensor head)		
Pin	Line color 1*	Line color 2*	Pin/wire function definition	Pin	Line color 3*	Pin/wire function definition
1	Blue	Grey	No. 1 magnet ring position signal(+)	1	Yellow	Current output
2	Green	Pink	No. 1 magnet ring position signal(-)	2	Grey	0Vdc(Current/Voltage Loop)
3	Yellow	Yellow	Reservation	3	Pink	Reservation
4	White	Green	Reservation	4	-	Reservation
5	Red	Brown	+24Vdc power supply (-20%~+20%)	5	Green	0...10V
6	Black	White	0 Vdc (power supply circuit)	6	Blue	0 Vdc (power supply circuit)
				7	Brown	+24Vdc power supply (-20%~+20%)
				8	White	Reservation

**Note:** \* Line color 1: cable PUR sheath, orange, -20~90 °C  
\* Line color 2/3: cable PVC sheath orange, -20~105 °C

## X Selection Guide - Analog Output

R   - M      -   -     -     -   -

01 02      03 04 05 06 07      08 09      10 11 12 13      14 15 16 17      18 19      20 21

01 - 02		Sensor shell form
R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

03 - 07		Measuring range
		Four digits, less than four digits are preceded by zero, M means metric system, unitmm

08 - 09		Magnet ring type / mounting thread form
Only for RH series	S 1	M18×1.5, measuring rod diameter 10mm, 304 material
	S 2	M20×1.5, measuring rod diameter 10mm, 304 material
	S 3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material
Only for RP series	C 1	Sector magnet
	C 2	Slider magnet
	C 3	Square magnet

10 - 13		Connection form
10 - 11		Cable outlet mode
D	H	PUR sheath, orange, -20~90℃, end scattered, line color 1
D	U	PVC sheath, orange, -20~105℃, end scattered, line color 2
D	B	PVC sheath, orange, -20~105℃, end scattered, line color 3
D	I	PUR sheath, orange, -20~90℃, end with 6-pin connector
D	V	PVC sheath, orange, -20~105℃, end with 6-pin connector
D	C	PVC sheath, orange, -20~105℃, end with 8-pin connector

12 - 13		Cable outlet mode: cable length, 01~99 meters
---------	--	---

**Note:** For supporting cables, please refer to Analog/Start-Stop Cable Accessories Selection

10 - 13		Connector mode
P	H 6 0	M16 male connector (6-pin)
P	B 8 0	M16 male connector (8-pin)

14 - 17		Signal output mode
---------	--	--------------------

14 - 15		Output form and direction
A	0	Current output, 4 ~ 20mA
A	1	Current output, 20 ~ 4mA
A	2	Current output, 0 ~ 20mA
A	3	Current output, 20 ~ 0mA
V	0	Voltage output, 0 ~ 10V
V	1	Voltage output, 10 ~ 0V
V	2	Voltage output, -10 ~ +10V
V	3	Voltage output, +10 ~ -10V
V	4	Voltage output, 0 ~ 5V
V	5	Voltage output, 5 ~ 0V
V	6	Voltage output, -5 ~ +5V
V	7	Voltage output, +5 ~ -5V

16		Number of magnet rings
1		Single magnet ring

17		No magnet ring state
A		Keep the original value
B		Maximum value
C		Minimum value

18 - 19		Non-usable area at head and end, customizable
S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)

20-21		Country
<input type="text"/>	<input type="text"/>	Refer to the country list, page 130.

Note: The forward output of the sensor means that when the magnet ring moves away from the electronic bin, the output value increases and decreases when the magnet ring moves in the reverse direction.

Selection example : RH-M0800-S1-DH02-A01C-S0-CN

Indicates: the ordered product model is RH structural displacement sensor, the measuring range is 800mm, and the mounting thread form is M18×1.5; the diameter of the measuring rod is 10mm, and the material is 304; cable outlet connection, 2m long PUR orange cable end scattered; 4~20mA current output; no magnet ring display value is the minimum value; single magnet ring; the non-usable area of the first end is 50.8mm, and the non-usable area of the end is 63.5mm.

## M M Selection of Analog/Start-Stop Cable Fittings

A S T - M    -     
 01 02 03 04 05 06 07 08 09 10

01 - 03			Type
A	S	T	Analog/Start-Stop interface
04 - 07			Cable length
M	*	*	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10			Cable type and outlet mode
H	0	1	One end of 6-pin (M16) female connector, and one end scattered
H	0	3	One end of 6-pin (M16) right angle female connector, and one end scattered
U	0	1	One end of 6-pin (M16) female connector, and one end scattered
U	0	2	One end of 8-pin (M16) female connector, and one end scattered
U	0	3	One end of 6-pin (M16) right angle female connector, and one end scattered
U	0	4	One end of 8-pin (M16) right angle female connector, and one end scattered
Note			H: cable type, PURsheath, orange, -20~90 °C
			U: Cable type, PVCsheath, orange, -20~105 °C

- Selection example: AST-M005-H01

Indicates: Analog or Start-Stop interface cable, cable length 5 meters, PURsheath, orange, -20~90°C, one end of the cable is 6-pin (M16) vcvfemale connector, and one end scattered.

- Selection example:AST-M010-U04

Indicates: Analog or Start-Stop interface cable, cable length 10 meters, PVC sheath, orange, -20~105°C, one end of the cable is an 8-pin (M16) right angle female connector, and one end scattered.



## RH/RP Displacement Sensor - SSI Output



### Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Linear measurement, absolute output
- High resolution, up to 0.1 $\mu$ m
- Easy diagnosis, LEDs real-time condition monitoring
- Repeatability is less than 0.001%FS
- Digital technology, stable and reliable
- Real-time induction and synchronous measurement
- Direct SSI signal output can directly replace encoder





## CC Product Parameters - SSI Output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500 mm, customized according to customer needs
Number of measurements	1

### • Output

Interface	SSI Synchronous Serial Interface				
Data Format	Binary or Gray code				
Data length	24/25/26bit				
Resolution	0.1/0.5 / 1 / 2 / 5 / 10 / 20 / 40/ 50 / 100 $\mu$ m				
Nonlinearity	< $\pm$ 0.01% of full scale, minimum $\pm$ 50 $\mu$ m				
Repetition accuracy	< $\pm$ 0.001% of full scale, minimum $\pm$ 1 $\mu$ m				
Transmission rate	50KBD~1MBD				
	line length	<3	<50	<100	<200 <400 (m)
	Rate	1000	<400	<300	<200 <100 (KBD)
Update time (High update rate)	Stroke:	300	750	1000	2000 5000 mm
	Frequency:	3.7	3.0	2.3	1.2 0.5 kHz
Update time (general)	1KHz (range $\leq$ 1m) 500Hz (1m < range $\leq$ 2m)				
	250Hz (2m < range $\leq$ 3m), customizable				
Hysteresis	<10 $\mu$ m				
Temperature coefficient	<15ppm/°C				

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67RH Stainless Stell Rod/IP65RP Aluminum profile
Operating temperature	-40°C ~ +85°C
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC Test	GB/T17626.2/3/4/6/8, Grade4/3/4/3/3, Class A, CE Certification

### • Structure and Materials

Failure indication	Electronic bin coverwith LEDs display	
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa (continuous)/70MPa (peak) or 350bar continuous)/700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
Mounting thread form	M18×1.5、 M20×1.5、 3/4"-16UNF-3A (customizable)	
Installation direction	Any direction	
Outgoing mode	Cable outlet or Connector	


### • Electrical Connections

Input voltage	+24Vdc $\pm$ 20%
Operating current	< 80mA (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	> 10M $\Omega$
Insulation strength	500V


## SS Output Characteristics-SSI Output

- SSI output magnetostrictive displacement sensor can provide Synchronized Serial Interface (SSI), which can convert the real-time position of vernier magnet into 24-bit, 25-bit or 26-bit (binary or Gray code) serial data format, and transmit the data to the controller by serial communication after receiving the clock signal provided by the controller. The format of SSI output data is identical to absolute output encoder, and it can be directly connected with PLC function modules (such as SM338 or SM138 of Siemens), which can be conveniently used to replace absolute encoder.

Timing diagram




Logic diagram



## LED Real-time State Monitoring and Diagnosis

- Red and green LEDs built into the sensor head cover provide sensor working condition and diagnostic function.

Green light	ON	ON	Flash
Red light	OFF	ON	ON
Function	Normal work	The magnet leaves the Stroke length range or the magnet cannot be detected	Programming state



## B Programming

- The TEC sensor can be programmed in the field using a USB converter. No needs to open the electronic bin, USB port power supply, standard cable connection, fully meet the needs of customers. The following parameters of the sensor can be modified by the configuration software of PC; Set sensor parameters (data length, data format, measurement direction); Graphical display of magnet position value; The user arbitrarily sets the sensor zero point and the measurement display value; Diagnose the sensor online by error code.



Sensor Programming Window


## A a Installation Instructions SSI Output

SSI output magnetostrictive linear displacement sensor provides synchronous serial signal output, which can convert the real-time position of vernier magnet into 24, 25 or 26-bit (binary or Gray code) data form, and transmit the data to the controller by serial communication after receiving the clock signal provided by the controller. The data format of SSI output is identical with absolute output encoder, and it can be connected directly with the function module of PLC, so it can be conveniently used to replace absolute encoder.

### • Dimensions and installation guidance of RH pressure-resistant rod sensor


RH series pressure-resistant rod shell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode, mounting thread form M18×1.5 or M20×1.5 or 3/4" -16UNF-3A.

Note: The measurement non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The default values of the first and last measurement non-usable areas of this product are 50.8mm and 63.5mm respectively. The value of the measurement non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.











### • Dimensions and installation guidance of RP aluminum profile sensor

RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.



**C** Common Accessories - SSI Output

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard Magnet ring Order No.: 211501		Magnetic isolation gasket		7-pin Female Connector Order No.: 312703	
Sector magnet Order No.: 211502		Sector magnetic isolation gasket		7-pin 90 Female Connector Order No.: 312704	
Slider magnet Order No.: 211503		Square magnet Order No.: 211508			

**Note:** Please refer to "Magnet ring Selection" for details of magnet ring kit and other models.

## • Wiring mode

When the sensor is connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet output, refer to the line color definition in the following table for connection mode



## • 7-pin male connector arrangement (facing the sensor head)

Pin	Line color 1*	Line color 2*	Pin/wire function definition
1	White	Grey	Data (-)
2	Yellow	Pink	Data (+)
3	Blue	Yellow	Clock (+)
4	Green	Green	Clock (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc
7	-	-	Do not connect



## • 8-pin male connector arrangement (facing the sensor head)

Pin	Line color 3*	Pin/wire function definition
1	Yellow	Clock (+)
2	Grey	Data (+)
3	Pink	Clock (-)
4	-	Reservation
5	Green	Data (-)
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

**Note:** \* Line color 1: cable PUR sheath, orange, -20~90℃  
\* Line color 2/3: Cable PVC sheath, orange, -20~105℃

## C Selection Guide-SSI Output

R 01 02 - M 03 04 05 06 07 - 08 09 10 11 12 - S 13 14 15 16 17 18 19 - 20 21 - 22 23

### 01 - 02 Sensor shell form

R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

### 03 - 07 Measuring range

Four digits, less than four digits are preceded by zero, M means metric system, unitmm

### 08 - 09 Magnet ring Type / Mounting Thread Form

Only for RH series	S	1	M 18×1.5, measuring rod diameter 10mm, 304 material
	S	2	M20×1.5, measuring rod diameter 10mm, 304 material
	S	3	3/4 "-16UNF-3A, measuring rod diameter 10mm, 304 material
Only for RP series	C	1	Sector magnet
	C	2	Slider magnet
	C	3	Square magnet

### 10 - 13 Connection form

#### 10- 11 Cable outlet mode

D	H	PUR sheath, orange, -20~90℃, end scattered, line color 1
D	U	PVC sheath, orange, -20~105℃, and one end scattered, line color 2
D	B	PVC sheath, orange, -20~105℃, and one end scattered, line color 3
D	I	PUR sheath, orange, -20~90℃, end with 6-pin connector
D	V	PVC sheath, orange, -20~105℃, end with 6-pin connector
D	C	PVC sheath, orange, -20~105℃, end with 8-pin connector

Note: See SSI cable accessories selection for supporting cables

### 12 - 13 Cable outlet mode: cable length, 01~99 meters

### 10 - 13 Connector mode

P	H	7	0	M16 male connector (7-pin)
P	B	8	0	M16 male connector (8-pin)

### 14 - 19 Signal output mode

#### 15 Data length

1	24-bit	2	25-bit	3	26-bit*
* 26-bit parity bits and 25-bit status bits					

#### 16 Data Format

B	Binary	G	Gray code
---	--------	---	-----------

#### 17 Resolution

1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm	8	0.04mm
9	0.0005mm	0	0.0001mm

#### 18 Direction

0	Forward	1	Reverse
---	---------	---	---------

#### 19 Mode

0	Regular	1	Synchronization	2	High update rate
---	---------	---	-----------------	---	------------------

### 20 - 21 Non-usable area at head and end, customizable

S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)

### 22 - 23 Country


		Refer to the country list, page 130.
--	--	--------------------------------------

- Note: The forward output of the sensor means that when the magnet ring moves away from the electronic bin, the output value increases and decreases when the magnet ring moves in the reverse direction.

- Selection example: RH-M0500-S1-PH70-S2B700-S0-CN

Indicates: The ordered product model is RH series displacement sensor, the measuring range is 500mm, the mounting thread form is M18×1.5, the measuring rod diameter is 10mm, 304 material, 7-pin M16 connector connection, no cable, SSI output (data bit length is 25-bit, output format is binary, resolution is 0.001mm, forward output, asynchronous mode), and the head non-usable area is 50.8mm and the end non-usable area is 63.5mm.

SS SSI Cable accessories selection Guide




01 - 03	Type
S S I	SSI interface

04 - 07	Cable length
M * * *	Less than 3 digits are preceded by zeros, and M means metric system, unit m

08 - 10	Cable type, outlet mode
H 0 1	One end of 7-pin (M16) is female connector, and one end scattered
H 0 3	One end of 7-pin (M16) right angle female connector, and one end scattered
U 0 1	One end of 7-pin (M16) is female connector, and one end scattered
U 0 2	One end of 8-pin (M16) is female connector, and one end scattered
U 0 3	One end of 7-pin (M16) right angle female connector, and one end scattered
U 0 4	One end of 8-pin (M16) right angle female connector, and one end scattered

Note	H: Cable type, PURsheath, orange, -20~90℃ U: Cable type, PVC sheath, orange, -20~105℃
------	--

- Selection example: SSI-M005-H01  
Indicates: SSI interface cable, cable length 5 meters, PURsheath, orange, -20~90℃, one end of the cable is 7-pin (M16) female connector, and one end scattered.
- Selection example: SSI-M010-U04  
Indicates: SSI interface cable, cable length 10 meters, PVC sheath, orange, -20~105℃, one end of the cable is an 8-pin (M16) right angle female connector, and one end scattered.



# RH/RP Displacement Sensor- Profibus-DP Bus Output



## Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Linear measurement, absolute output
- High resolution, up to 5µm
- Easy diagnosis, LEDs real-time condition monitoring
- Repetition accuracy is less than 0.001% F.S
- Digital technology, stable and reliable
- Direct Profibus-DP signal output
- Supports simultaneous measurement of multiple magnet ring positions

## T t Product parameters-Profibus-DP bus output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500 mm, customized according to customer needs
Number of measurements	1~9

### • Output

Interface	Profibus-DP System, ISO74498
Data format	Profibus-DP (EN-50170)
Transmission speed	Maximum 12Mbit/s
Resolution	1 / 5 / 10 / 20 / 50 / 100 $\mu$ m
Nonlinearity	$\pm 0.01\%$ of full scale, minimum $\pm 50\mu$ m
Repetition accuracy	$\pm 0.001\%$ of full scale, minimum $\pm 1\mu$ m
Update time	1KHz (range $\leq 1$ m) 500Hz ( $1\text{m} < \text{range} \leq 2$ m) 250Hz ( $2\text{m} < \text{range} \leq 3$ m), customizable
Hysteresis	$< 10\mu$ m
Temperature coefficient	$< 15\text{ppm}/^\circ\text{C}$

### • Structure and Material

Failure indication		Electronic bin coverwith LEDs display
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa(continuous)/70MPa(peak)or 350bar(continuous)/700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
Mounting thread form		M18×1.5、 M20×1.5、 3/4"-16UNF-3A (customizable)
Installation direction		Any direction
Outgoing mode		Cable outlet or Connector

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67RH Stainless Stell Rod/IP65RP Aluminum profile
Operating temperature	$-40^\circ\text{C} \sim +85^\circ\text{C}$
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification


### • Electrical connection

Input voltage	+24Vdc $\pm 20\%$
operating current	$< 80\text{mA}$ (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	$> 10\text{M}\Omega$
Insulation strength	500V




## SS Output Characteristics-Profibus-DP Bus Output


- Connection by 5-pin connector (series connection): The power supply cable is separate from the bus connection.



- Connection by 5-pin connector (parallel connection): a standard T connector with cable for bus connection, the power supply cable is separate. When any sensor on the line is disconnected, the sensors on other lines keep working.




- Connection with a 6-pin connector (series connection)



## LU LED Real-time State Monitoring and Diagnosis

- The integrated LEDs (red or green) provide the basic status feedback and troubleshooting function of the sensor.

Green light	ON	ON	Flash	Flash
Red light	OFF	ON	OFF	ON
Function	Normal work	Magnets not detected or incorrect number	Waiting for host parameters	Programming state



## Bb Programming

- The TEC sensor can be programmed in the field using a USB converter. No need to open the electronic bin, USB port power supply, standard cable connection, fully meets the needs of customers. The following parameters of the sensor can be modified by the configuration software of PC: setting the slave station address; Graphical display of magnet ring position value; Diagnose the sensor online by error code.



USB Converter  
(Order No. TEC612814)



Sensor Programming Window

## A a Installation and Use Instructions - Profibus-DP Bus Output


The DP output magnetostrictive sensor meets the Profibus-DP (EN 50 170) protocol. The sensor transmits the absolute position data of the magnet ring to the controller in the form of RS-485 standard serial asynchronous, and the maximum transmit rate can reach 12Mbps. The Profibus-DP interface provides powerful diagnostic and setting functions in the form of GSD data sheets.

- Dimensions and installation guidance of RH pressure-resistant rod sensor


RH series pressure-resistant rodshell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode, mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The default values of the first and last measurement Non-usable areas of this product are 50.8mm and 63.5mm respectively. The value of the measurement Non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.


Cable outlet



Six pin Connector



Five pin Connector




## A a Installation Instructions-Profibus-DP Bus Output

### • Dimensions and installation guidance of RP aluminum profile sensor


RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The default value of the measurement Non-usable area at the head and end is 28mm and 66mm respectively. The value of the measurement Non-usable area can be modified appropriately according to the customer's needs, please pointed out when ordering.


#### Cable outlet




















#### Six pin Connector



#### Five pin Connector




**C Common Accessories-Profibus-DP Bus Output**

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard Magnet ring Order No.: 211501		Magnetic isolation gasket Order No.: 211501		5-pin connector male head (B code) Order No.: 312706	
Sector magnet Order No.: 211502		Sector magnetic isolation gasket Order No.: 211502		5-pin female connector (B code) Order No.: 312707	
Slider magnet Order No.: 211503		Square magnet Order No.: 211508		5-pin T-shaped male connector Order No.: 312708	
Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
5-pin 90° Connector male Order No.: 312709		6-pin Connector male Order No.: 312714		4-pin Female Connector (For power supply) Order No.: 522000-XX xx-cable length in m	
5-pin 90° female connector Order No.: 312710		6-pin female connector Order No.: 312701		4-pin 90° female connector (For power supply) Order No.: 522001-XX xx-cable length in m	
5-pin end connector Order No.: 312705		6-pin end male connector Order No.: 312715			

Note: Please refer to "Magnet ring Selection" for details of magnet ring kit and other models.

**• Wiring mode**


When the sensor is connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet output, refer to the line color definition in the following table for connection mode



4-pin connector socket (for power supply)


**• 4-pin male connector pin arrangement (facing the sensor head direction)**

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc power supply (-20%+20%)
2	White	Do not connect
3	Blue	0Vdc(power supply circuit)
4	Black	Do not connect

**• 5-pin male connector, female connector pin arrangement (facing the direction of the sensor head)**

Pin	Line color	Pin/wire function definition
1	-	VP+5N(applicable to end wiring only) *
2	Green	RxD/TxD-N(Bus)
3	-	DGnd(end connection only) *
4	Red	RxD/TxD-P(Bus)
5	Shielded wire	Ground the cable shield wire


Note: \* Only applicable to signal connection of sensor female connector

**• 6-pin male connector, female connector pin arrangement (facing the direction of the sensor head)**

Pin	Line color	Pin/wire function definition
1	Green	RxD/TxD-N(bus)
2	Red	RxD/TxD-P(bus)
3	-	DGnd(for end wiring only) *
4	-	VP+5N(for end wiring only) *
5	Black	+24Vdc power supply (-20%+20%)
6	Blue	0 Vdc (power supply circuit)

Note: \* Only applicable to signal connection of sensor female connector

## X Selection Guide-Profibus-DP Bus Output



### 01 - 02 Sensor shell form

R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

### 03 - 07 Measuring range

Four digits, less than four digits are preceded by zero, M means metric system, unitmm

### 08 - 09 Magnet ring type/mounting thread form

Only for RH series	S	1	M18×1.5, measuring rod diameter 10mm, 304 material
	S	2	M20×1.5, measuring rod diameter 10mm, 304 material
	S	3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material
Only for RP Series	C	1	Sector magnet
	C	2	Slider magnet
	C	3	Square magnet

### 10 - 13 Connection form

#### 10 - 11 Cable outlet mode

D	A	Single cable outlet, PUR sheath, cyan, -20~80C, end scattered
D	B	Double cable outlet, PUR sheath, cyan, -20~80°C, end scattered
D	C	Double cable outlet, PUR sheath, cyan, -20~80°C, M16, 6-pin, end with a male connector and a female connector

#### 12 - 13 Cable outlet: cable length, 01 to 99 meters

#### 10 - 13 Connector mode

P	D	5	3	One set of 5-pin male connector (M12), one set of 5-pin female connector (M12), One set of 4-pin male connectors (M8)
P	D	6	3	One set of 6-pin male connectors (M16), one set of 6-pin female connectors (M16)

**Note:** See SSI cable accessories selection for supporting cables

### 14 - 16 Signal output mode

14	Profibus Protocol
15	Number of magnet rings (1~9 optional)
16	0-single magnet B-single/multiple magnet rings

### 17 - 18 Non-usable area at head and end, customizable

S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)

### 19 - 20 Country

		Refer to the country list, page 130.
--	--	--------------------------------------

- Note: The forward output of the sensor means that when the magnet ring moves away from the electronic bin, the output value increases and decreases when the magnet ring moves in the reverse direction.
- Selection example: RH-M0300-S1-PD53-D10-S0-CN  
Indicates: The ordered product model is RH structure displacement sensor, with a measuring range of 300mm, mounting thread form of M18×1.5 (metric system), measuring rod diameter of 10mm, 304 material, 5-pin Connector connection, Profibus signal output, single magnet ring, head end Non-usable area of 50.8mm and end Non-usable area of 63.5mm.

## P p Profibus-DP Cable Accessories Selection

D	P	—	M				—			
01	02		03	04	05	06		07	08	09

01 - 02	Type		
<table border="1"><tr><td>D</td><td>P</td></tr></table>	D	P	Profibus-DP interface
D	P		

03 - 06					Cable length
M	*	*	*	Less than 3 digits are preceded by zeros, and M means metric system, unit m	

07 - 09			Cable type、utlet mode
H	0	1	One end of 5-pin (M12) female connector, and one end scattered
H	0	2	One end of 5-pin (M12) female connector, and one end scattered
H	0	3	One end of 5-pin (M12) right angle female connector, and one end scattered
H	0	4	One end of 5-pin (M12) right angle maleconnector, and one end scattered
Z	0	5	One end of 6-pin (M16) female connector, and one end scattered
Z	0	6	One end of 6-pin (M16) female connector, and one end scattered
Z	0	7	One end of 6-pin (M16) right angle female connector, and one end scattered
H	1	2	One end of 5-pin (M12) female connector; One end of 5-pin (M12) female connector
H	3	4	One end of 5-pin (M12) right angle male connector; One end of 5-pin (M12) right angle female connector
Z	5	6	One end of 6-pin (M16) male connector and one end of 6-pin (M16) is female connector

Note	H: Cable type, PUR sheath, purple, 2 cores,-20~80℃
	Z: Cable type, PUR sheath, cyan, 5-pin,-20~80C℃

- Selection example: DP-M020-H01

Indicates: Profibus-DP interface cable, 20 meters long, PUR sheath, purple, 2 cores,-20~80℃, 5-pin (M12) at one end of the cable are female connector, and the other end is scattered.

- Selection example: DP-M015-Z56


Indicates: Profibus-DP interface cable, with a length of 15m, PUR sheath, cyan, 5 cores,-20~80℃, with 6-pin (M16) at one end male connector and 6-pin (M16) at the other end female connector.

# RH/RP Displacement Sensor- CANBus Output



## Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Linear measurement, absolute output
- High resolution, up to 1µm
- Easy diagnosis, LEDs real-time condition monitoring
- The repetition accuracy is 0.001% F.S
- Digital technology, stable and reliable
- CANopen signal output
- Support simultaneous measurement of multiple magnet ring positions



## CC Product Parameters-CAN Bus Output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500 mm, customized according to customer needs
Number of measurements	1~9

### • Output

Interface	CANBus System Protocol, ISO11898
CANopen	CIA Standard DS-301V3.0 Encoder Profile DS-406V3.1
Transmission speed	Maximum 1Mbit/s
Resolution	1 / 2 / 5 / 10 / 20 / 50 / 100 $\mu$ m
Nonlinearity	< 0.01% full-scale taxi, minimum 50 $\mu$ m
Repetition accuracy	< $\pm$ 0.001% of full scale, minimum $\pm$ 1 $\mu$ m
Update time	1KHz ( range $\leq$ 1m) 500Hz (1m< range $\leq$ 2m) 250Hz (2m< range $\leq$ 3m) , customizable
Hysteresis	<10 $\mu$ m
Temperature coefficient	<15ppm/ $^{\circ}$ C

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67RH Stainless Stell Rod/IP65RP Aluminum profile
Operating temperature	-40 $^{\circ}$ C ~ +85 $^{\circ}$ C
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC Test	GB/T17626.2/3/4/6/8, Grade4/3/4/3/3, Class A, CE Certification

### • Structure and Material

Failure indication		Electronic bin coverwith LEDs display
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa (continuous )/70MPa (peak) or 350bar (continuous)/700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
Mounting thread form		M18×1.5、 M20×1.5、 3/4"-16UNF-3A (customizable)
Installation direction		Any direction
Outgoing mode		Cable outlet or Connector


### • Electrical Connection

Input voltage	+24Vdc $\pm$ 20%
operating current	<80mA (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	> 10M $\Omega$
Insulation strength	500V



## SS Output Characteristics-CAN Bus Output


- Connect by 6-pin connector (series connection)



## LU LED Real-time State Monitoring and Diagnosis

- As a slave station, CAN output magnetostrictive displacement sensor can upload the displacement information and velocity information of the vernier magnet to the controller in real time through bus. It conforms to CAN (ISO 11898) protocol standard, and the maximum transmission rate is 1Mbit/s.
- The integrated LEDs (red or green) provide the basic status feedback and troubleshooting function of the sensor.

Green light	ON	ON	ON	Flash
Red light	OFF	Flash	ON	ON
Function	Normal work	The magnet leaves the Stroke length range	Magnet not detected	Programming state







## A a Installation Instructions-CAN Bus Output

- Dimensions and installation guidance of RH pressure-resistant rod sensor

RH series pressure-resistant rodshell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode, mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The values of the head and end non-usable areas of this product are 50.8mm and 63.5mm respectively. The value of the measurement non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.











## A a Installation Instructions-CAN Bus Output









### • Dimensions and installation guidance of RP aluminum profile sensor

RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The default value of the measurement Non-usable area at the head and end of this product is 28mm and 66mm respectively. The value of the measurement Non-usable area can be modified appropriately according to the customer's needs, please pointed out when ordering.




**C Common Accessories - CAN Bus Output**

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard Magnet ring Order No.: 211501		Magnetic isolation gasket		6-pin female connector Order No.: 312701	
Sector magnet Order No.: 211502		Sector magnetic isolation gasket		6-pin end female connector Order No.: 312722	
Slider magnet Order No.: 211503		Square magnet Order No.: 211508			

**Note:** Please refer to "Magnet ring Selection" for details of magnet ring kit and other models.

**• Wiring mode**


When the sensor is connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet output, refer to the line color definition in the following table for connection mode

**• 5-pin male connector and female connector pin arrangement (facing the sensor head direction)**

Pin	Line color	Pin/wire function definition
1	-	Do not connect
2	Brown	+24 Vdc power supply (-20%~+20%)
3	White	0Vdc (power supply loop)
4	Yellow	CAN (+)
5	Green	CAN (-)

**• 6-pin male connector arrangement (facing the sensor head)**

Pin	Line color	Pin/wire function definition
1	Green	CAN (-)
2	Yellow	CAN (+)
3	-	Do not connect
4	-	Do not connect
5	Brown	+24Vdc power supply (-20%~+20%)
6	White	0 Vdc (power supply loop)



4-pin connector socket (for power supply)

**• 4-pin male connector pin arrangement (facing the sensor head direction)**

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc power supply (-20%+20%)
2	White	Do not connect
3	Blue	0Vdc(power supply circuit)
4	Black	Do not connect

## X Selection Guide-CAN Bus Output

R 01 02 - M 03 04 05 06 07 - 08 09 - 10 11 12 13 - C 14 15 16 17 18 - 19 20 - 21 22

### 01 - 02 Sensor shell form

R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

### 03 - 07 Measuring range

Four digits, less than four digits are preceded by zero, M means metric system, unitmm

### 08 - 09 Magnet ring type/mounting thread form

Only for RH series	S	1	M 18×1.5, measuring rod diameter 10mm, 304 material
	S	2	M20×1.5, measuring rod diameter 10mm, 304 material
	S	3	3/4 "-16UNF-3A, measuring rod diameter 10mm, 304 material
Only for RP Series	C	1	Sector magnet
	C	2	Slider magnet
	C	3	Square magnet

### 10 - 13 Connection form

### 10 - 11 Cable outlet mode

D	A	Single cable outlet, PUR sheath, cyan,-20~80C, end scattered
---	---	--

### 12 - 13 Cable outlet mode: cable length, 0199 meters

0	D	R	1	PVC sheath, length 150mm, end 5 pin male connector
---	---	---	---	--

### 10 - 13 Connector mode

P	D	6	0	6-pin male connector (M16)
P	D	6	2	Two sets of 6-pin male connectors (M16)
P	D	5	0	5-pin male connector (M12)
P	D	5	2	5-pin male connector (M12) and 5-pin female connector (M12)
P	D	5	4	5-pin male connectors (M12), 5-pin female connectors (M12), 4-pin male connectors (M8)

**Note:** For supporting cables, please refer to CAN bus cable accessories selection

### 14 - 18 Signal output mode

### 14 Interface

C	CAN bus
---	---------

### 15 Protocol type

1	CANopen	2	CANBasic
---	---------	---	----------

### 16 Baud

1	1000kBit/s	2	800kBit/s
3	500kBit/s	4	250kBit/s
5	125kBit/s	6	100kBit/s
7	50kBit/s	8	20kBit/s

### 17 Resolution

1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm		

### 18 Number of magnet rings (1~9 optional)

### 19 - 20 Non-usable area at head and end, customizable

S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)

### 21 - 22 Country

		Refer to the country list, page 130.
--	--	--------------------------------------

- Note: The forward output of the sensor means that when the magnet ring moves away from the electronic bin, the output value increases and decreases when the magnet ring moves in the reverse direction.

- Selection example: RH-M0300-S1-PD60-C1171-S0-CN

Indicates: The ordered product model is RH structure displacement sensor, the measuring range is 300mm, the mounting thread form is M18×1.5 (metric system), the measuring rod diameter is 10mm, the material is 304, One set of 6-pin male connector, the baud is 1000kbit/s, the resolution is 0.001mm, single magnet ring, the Non-usable area at the head is 50.8mm, and the Non-usable area at the end is 63.5mm.

C Selection of CAN Bus Cable Accessories

C A N - M - -

01020304050607080910

01 - 03	Type
C A N	CAN bus
04 - 07	Cable length
M * * *	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10	Cable type, outlet mode
08	Cable type
C	PVC sheath, purple, 4 cores,-40~75C
09 - 10	Connection
0 1	One end of 6-pin (M16) female connector, and one end scattered
0 2	One end of 5-pin (M12) female connector, and one end scattered
0 3	One end of 5-pin (M12) male connector, and one end scattered
0 4	One end of 5-pin (M12) right angle female connector, and one end scattered
0 5	One end of 6-pin (M16) right angle female connector, and one end scattered
1 1	6-pin (M16) female connector at both ends
2 3	One end 5-pin (M12) female connector and one end 5-pin (M12) male connector

- Selection example: CAN-M015-C01  
Indicates: CAN bus interface cable, 15m long, PVC sheath, purple, 4-pin,-40~75C, 6-pin (M16) at one end of the cable are female connector, and one end scattered.
- Selection example: CAN-M020-C23  
Indicates: CAN bus interface cable, 20 meters long, PVC sheath, purple, 4 cores,-40~75C, with 5-pin (M12) at one end female connector and 5-pin (M12) at the other end male connector.




# RH/RP Displacement Sensor - Profinet Output



## Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Linear measurement, absolute output
- Nonlinearity less than 0.01%
- Easy diagnosis, LEDs real-time condition monitoring
- The repetition accuracy is less than 0.001%
- Digital technology, stable and reliable





## C Product Parameters-Profinet Output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500 mm, customized according to customer needs
Number of measurements	1~9

### • Output

Interface	Profinet IO RT
Data protocol	TEC Profile and Encoder Profile 4.1
Transmission speed	Maximum 100Mbit/s
Resolution	1 / 2 / 5 / 10 / 20 / 50 / 100 $\mu$ m
Nonlinearity	$\leq \pm 0.01\%$ of full scale, minimum $\pm 50\mu$ m
Repetition accuracy	$< 0.001\%$ for full-scale taxis, minimum $\pm 1\mu$ m
Update time	1KHz (range $\leq 1$ m) 500Hz ( $1\text{m} < \text{range} \leq 2$ m) 250Hz ( $2\text{m} < \text{range} \leq 3$ m), customizable
Hysteresis	$< 10\mu$ m
Temperature coefficient	$< 15\text{ppm}/^\circ\text{C}$

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67RH Stainless Stell Rod/IP65RP Aluminum profile
Operating temperature	$-40^\circ\text{C} \sim +85^\circ\text{C}$
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC Test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Structure and Material

Failure indication		Electronic bin cover with LEDs display
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa (continuous)/70MPa (peak) or 350bar ( continuous)/700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
Mounting thread form		M18×1.5、 M20×1.5、 3/4"-16UNF-3A (customizable)
Installation direction		Any direction
Outgoing mode		Cable outlet or Connector

### • Electrical Connection


Input voltage	+24Vdc $\pm 20\%$
operating current	$< 90\text{mA}$ (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	$> 10\text{M}\Omega$
Insulation strength	500V

## A a Installation Instructions-Profinet Output

### • RH pressure-resistant rod mounting dimensions

RH series pressure-resistant rodshell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode, mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.


Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The values of the head and end Non-usable areas of this product are 50.8 m and 63.5 m respectively. The value of the measurement Non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.
















Note: With standard magnet ring kit 288501, with magnetic insulation gasket and fixing screw; Plug 321723 when Connector is equipped with cable plug

### • Dimensions and installation guidance of RP aluminum profile sensor

RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.



**C** Common Accessories-Profinet Output

Accessory name/ model		Dimensions	
4-pin female connector (For power supply) Order No.: 522000-xx (xx- cable length, unit m)			
4-pin90° female connector (For power supply) Order No.: 522001-xx (xx- cable length, unit m)			
For power supply (Cat 5e) d-coded Order No.: 522004-xx (xx- cable length, unit m)		 Connector type: two 4-pin 90° male connectors (M12) Cable sheath: PVC, light blue operating temperature:-40 C ~80 C	
Accessory name/ model		Dimensions	
For power supply (Cat 5e) d-coded Order No.: 522005-xx (xx- cable length, unit m)		 Connector type: RJ45, 4-pin 90° male connector (M12) Cable sheath: PVC, light blue working temperature:-40 C ~80 C	
For power supply (Cat 5e) d-coded Order No.: 522006-xx (xx- cable length, unit m)		 Connector Type: RJ45, 4-pin straight male connector(M12) Cable sheath: PVC, light blue Working temperature:-40 C ~80 C	
For power supply (Cat 5e) d-coded Order No.: 522008-xx (xx-cable length, unit m)		 Connector type: Two straight male connectors (M12) Cable sheath: PVC, light blue Working temperature:-40 C ~80 C	
Accessory name/ model		Dimensions	
Standard magnet ring Order No.: 211501			
Sector magnet Order No.: 211502			
Slider magnet Order No.: 211503			
Square magnet Order No.: 211508			
Accessory name/ model		Dimensions	
Magnetic isolation gasket			
Sector magnetic isolation gasket			
4-pin male connector Order No.: 312723			

**Note:** Please refer to "Magnet ring Selection" and "Cable Selection" for details of cables, magnet rings and other models.

## • Wiring mode



4-pin connector socket  
(for power supply)

• Connector Connection Mode (Interface 1, 2)		
Pin	Line color	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -
• Single cable outlet connection mode		
Pin	Line color 1*	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -
5	Red	24Vdc
6	Black	COM

• Connector Connection Mode (Interface 3)			
Pin	Line color	Pin/wire function definition	
1	Brown	+24Vdc (-20%~+20%)	
2	White	Do not connect	
3	Blue	COM	
4	Black	Do not connect	
• Double cable outlet connection mode			
Pin	Line color1*	Line color2*	Pin/wire function definition
1	Yellow	Yellow	Tx +
2	White	White	Rx +
3	Orange	Orange	Tx -
4	Blue	Blue	Rx -
5	Red	-	24Vdc
6	Black	-	COM

**Note:** \* Line color 1: light green, PUR sheath, 6 cores,-40C~85 C

**Note:** \* Line color 2: light green, PUR sheath, 4 cores,-40C~70 C

## X Selection Guide-Profinet Output

R		-	M					-			-					-	N			-			-		
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16		17	18		19	20

01 - 02		Sensor shell form
R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

03 - 07		Measuring range
		Four digits, less than four digits are preceded by zero, M means metric system, unit: mm

08 - 09		Magnet ring type/mounting thread form
Only for RP Series	S 1	M18×1.5, measuring rod diameter 10mm, 304 material
	S 2	M20×1.5, measuring rod diameter 10mm, 304 material
	S 3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material
Only for RP Series	C 1	Sector magnet
	C 2	Slider magnet
	C 3	Square magnet

10 - 13		Connection form
D	A * *	Single cable outlet, light green, PUR sheath (6 cores), -40C~85℃ ( * * denotes cable length in meters)
D	B * *	Double cable outlet, light green, PUR sheath (one set of 6 cores, -40C~85C; one set of 4 cores, -40 C~70C) ( * *denotes cable length in meters)
P	D 5 6	two sets of 4-pin M12 female connectors, one set of 4-pin M8 male connector

**Note:** For supporting cables, please refer to the Selection Guide of Industrial Ethernet Cable Accessories

14 - 16		Communication interface
14	N	Profinet communication interface
15		Number of magnet rings (1~9 optional)
16		0-General, customizable

17 - 18		Non-usable area at head and end, customizable
S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)

19 - 20		Country
		Refer to the country list, page 130.

### ● Selection example: RH-M0300-S1 -PD56-N10-S0

Indicates: RH structure series, 300mm Stroke length, M18X1.5 mounting thread, measuring rod diameter 10mm, 304 material, 2 sets of 4-pin female connectors, M12, 1 set of 4-pin male connector, M8, Profinet protocol, single magnet ring, head Non-usable area 50.8mm, end Non-usable area 63.5mm.

## G Selection of Cable Accessories for Industrial Ethernet

NET - M - - - -

01 02 03 04 05 06 07 08 09 10

01 - 03	Type
N E T	Industrial Ethernet
04 - 07	Cable length
M * * *	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10	Cable type, outlet mode
08	Cable type
D	PVC sheath, blue, 8-pin, shielded, CAT-5e,-40~85°C
A	PUR sheath, green, 4-pin, shielded, CAT-5eES,-40~70C
09 10	Connection
1 1	Two 4-pin connector, M12, d-code
2 2	Two 4-pin right angle male connectors, M12, d-code
1 3	One end 4-pin connector, M12, d-code, one end shielded RJ45 connector
2 3	One end 4-pin right angle male connector, M12, d-code, one end shielded RJ45 connector

- Selection example: NET-M010-D11  
Indicates: Ethernet cable, 10m long, PVC sheath, blue, 8-pin, CAT-5e standard, shielded,-40~85C, 4-pin connector at both ends, M12, d-code.
- Selection example: NET-M020-A23  
Indicates: Ethernet cable, 20 meters long, PUR sheath, green, 4-pin, shielded, CAT-5eES,-40~70°C, 4-pin right angle male connector at one end of the cable, M12, d-code, and shielded RJ45 connector at one end.

## L LED real-time state monitoring and diagnosis

Green light	ON	ON	ON	Flash
Red light	OFF	ON	Flash	×
Function	Normal work	The network cable is not connected	Configuring	Fault



# RH/RP Displacement Sensor- Start/Stop Output



## Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Easy diagnosis, LEDs real-time condition monitoring
- No need to return to zero, absolute displacement output
- Stable and reliable, using digital analog technology
- Low power consumption design effectively reduces system heating



## C Product Parameters-Start/Stop Output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500 mm, customized according to customer needs
Number of measurements	Multiple

### • Output

Digital quantity	Start/Stop Signal (Start/End)
Resolution	Controller dependent (minimum accuracy 5μm)
Nonlinearity	< 0.01% full-scale taxi, minimum 50μm
Pulse width	Start pulse: 2~5μs, stop pulse: 1.5~2μs
Repetition accuracy	< 0.001% of full-scale taxis, min. 1μm
Update time	1KHz (range ≤ 1m) 500Hz (1m < range ≤ 2m) 250Hz (2m < range ≤ 3m), customizable
Hysteresis	< 10μm
Temperature coefficient	< 30ppm/°C

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67RH Stainless Steel Rod/IP65RP Aluminum profile
Operating temperature	-40 °C ~ +105 °C
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC Test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Structure and Material


Failure indication		Electronic bin cover with LEDs display
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa (continuous )/70MPa (peak) or 350bar ( continuous)/700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
Mounting thread form		M18×1.5、 M20×1.5、 3/4"-16UNF-3A (customizable)
Installation direction		Any direction
Outgoing mode		Cable outlet or Connector

### • Electrical Connection

Input voltage	+24Vdc±20%
operating current	< 90mA (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	> 10MΩ
Insulation strength	500V

## SS Output Characteristics-Start/Stop Output


- The sensor outputs the controller start signal and the position magnet signal, and the time interval between them is proportional to the displacement of the position magnet. The measurement and control of time is calculated by the controller and converted into displacement value.



## LL LED Real-time State Monitoring and Diagnosis

- Red and green LED indicator built into the sensor head cover provides sensor working condition and diagnostic function.

Green light	ON	ON	ON	Flash
Red light	OFF	Flash	ON	OFF
Function	Normal work	The sensor has no interrogation signal	Magnet not detected	Programming state






## A a Installation Instructions-Start/Stop Output

### • Dimensions and installation guidance of RH pressure-resistant rod sensor


RH series pressure-resistant rodshell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode, mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The values of the head and end Non-usable areas of this product are 50.8 m and 63.5 m respectively. The value of the measurement Non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.



### • Dimensions and installation guidance of RP aluminum profile sensor

RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.



## C Common Accessories-Start/Stop Output

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard magnet ring Order No.: 211501		Magnetic isolation gasket		6-pin female connector Order No.: 312701	
Sector magnet Order No.: 211502		Sector magnetic isolation gasket		6-pin 90° female connector Order No.: 312702	
Slider magnet Order No.: 211503		Square magnet Order No.: 211508			

**Note:** Please refer to "Magnet ring Selection" for details of magnet ring kit and other models.

### • Wiring mode

When the sensor is connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet output, refer to the line color definition in the following table for connection mode



#### • 6-pin male connector arrangement (facing the sensor head)

Pin	Line color 1*	Line color 2*	Pin/wire function definition
1	Blue	Grey	Stop (-)
2	Green	Pink	Stop (+)
3	Yellow	Yellow	Start (+)
4	White	Green	Start (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc

#### • 8-pin male connector arrangement (facing the sensor head direction)

Pin	Line color 3*	Pin/wire function definition
1	Yellow	Start (+)
2	Grey	Stop (+)
3	Pink	Start (-)
4	-	Reservation
5	Green	Stop (-)
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

**Note:** \* Line color 1: Cable PUR sheath, orange, -20~90 °C  
\* Line color 2/3: Cable PVC sheath, orange, -20~105 °C

**X x Selection Guide -Start/Stop Output**

R 01 02 - M 03 04 05 06 07 - 08 09 - 10 11 12 13 - R 14 15 16 17 - 18 19 - 20 21

**01 - 02 Sensor shell form**

R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

**03 - 07 Measuring range**

Four digits, less than four digits are preceded by zero, M means metric system, unitmm

**08 - 09 Magnet ring type/mounting thread form**

Only for RH series	S	1	M18×1.5, measuring rod diameter 10mm, 304 material
	S	2	M20×1.5, measuring rod diameter 10mm, 304 material
	S	3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material
Only for RP Series	C	1	Sector magnet
	C	2	Slider magnet
	C	3	Square magnet

**10 - 13 Connection form****10 - 11 Cable outlet mode**

D	H	PUR sheath, orange, -20~90° C, end scattered, line color 1
D	U	PVC sheath, orange, -20~105°C, end scattered, line color 2
D	B	PVC sheath, orange, -20~105°C, end scattered, line color 3
D	I	PUR sheath, orange, -20~90° C, end with 6-pin connector
D	V	PVC sheath, orange, -20~105°C, end with 6-pin connector
D	C	PVC sheath, orange, -20~105°C, end with 8-pin connector

**12 - 13 Cable length, 01~99 units: m (Cable outlet mode)****10 - 13 Cable outlet mode**

10 - 13	0	D	R		Cable outlet first and end with plastic connector
0	D	R	2		Scattered wire with plastic connector 65mm
0	D	R	3		Scattered wire with plastic connector 170mm
0	D	R	4		Scattered wire with plastic connector 230mm
0	D	R	5		Scattered wire with plastic connector 350mm

**10 - 13 Connector mode**

P	H	6	0	M16 male connector (6-pin)
---	---	---	---	----------------------------

**Note:** For supporting cables, please refer to Analog/Start-Stop Cable Accessories Selection

**14 - 17 Signal output mode****15 Input voltage**

1	+ 24Vdc ( - 20% ~ + 20% )
2	+ 9 ~ 28.8Vdc

**16 - 17 Output signal**

0	1	Start/Stop, multi-magnet ring
---	---	-------------------------------

**18 - 19 Non-usable area at head and end, customizable**

S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)

**0 1 Country**

		Refer to the country list, page 130.
--	--	--------------------------------------

● **Note:** The forward output of the sensor means that when the magnet ring moves away from the electronic bin, the output value increases and decreases when the magnet ring moves in the reverse direction.

● **Selection example:** RH-M0300-S1-PH60-R101-S0

Indicates: the ordered product model is RH series displacement sensor, the measuring range is 300mm, the mounting thread form is M18×1.5, the measuring rod diameter is 10mm, the material is 304, the 6-pin Connector connection, the power supply voltage is + 24Vdc, start/stop output, the head Non-usable area is 50.8mm, and the end Non-usable area is 63.5mm.

## Mm Selection Guide of Analog/Start-Stop Cable Fittings

A
S
T
-
M
 
 
 
-
 
 
 

01   02   03   04   05   06   07   08   09   10

01 - 03				Type
A	S	T		Analog/Start-Stop interface
04 - 07				Cable length
M	*	*	*	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10				Cable type, outlet mode
H	0	1		One 6-pin (M16) female connector, and one end scattered
H	0	3		One 6-pin (M16) right angle female connector, and one end scattered
U	0	1		One end 6-pin (M16) female connector, and one end scattered
U	0	2		One end 8-pin (M16) inserted into female connector, and one end scattered
U	0	3		One end 6-pin (M16) right angle female connector, and one end scattered
U	0	4		One end 8-pin (M16) right angle female connector, and one end scattered
Note				H: Cable type, PUR sheath, orange, -20~90 °C
				U: Cable type, PVC sheath, orange, -20~105 °C

- Selection example: AST-M005-H01

Indicates: analog or start-stop interface cable, 5 meters long, PUR sheath, orange, -20~90 °C, with 6-pin (M16) at one end female connector and scattered at one end.

- Selection example: AST-M010-U04

Indicates: Analog or Start-Stop interface cable, 10 meters long, PVC sheath, orange, -20~105 °C; One end 8-pin (M16) right angle female connector, and one end scattered.

# RH/RP Displacement Sensor- EtherCAT Output

---



## Technical Characteristics

---

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Linear measurement, absolute position output
- Easy diagnosis, LEDs real-time condition monitoring
- Nonlinearity less than 0.01%
- The repetition accuracy is less than 0.001%
- Up to 9 magnet position, speed, status information output

## CC Product parameters-EtherCAT output

### • Input

Measurement data	Position magnet ring
Stroke length	25~5500mm
Number of measurements	1~9

### • Output

Interface	EtherCAT Ethernet Control Automation Technology
Data protocol	EtherCAT 100 Base-TX
Transmission speed	Maximum 100Mbit/s
Resolution	1 ~ 100 $\mu\text{m}$ , adjustable
Nonlinearity	$<\pm 0.01\%$ of full scale, minimum 50 $\mu\text{m}$
Repetition accuracy	$<\pm 0.001\%$ of full scale, minimum $\pm 1\mu\text{m}$
Update time	$\geq 0.25\text{ms}$ , depending on the measuring stroke
Hysteresis	$<10\mu\text{m}$
Temperature coefficient	$<15\text{ppm}/^\circ\text{C}$

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP67RH Stainless Steel Rod/IP65RP Aluminum profile
Operating temperature	$-40^\circ\text{C} \sim +85^\circ\text{C}$
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC Test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Structure and Material

Failure indication		Electronic bin cover with LEDs display
RH Series	Electronic bin	Aluminum alloy
	Measuring rod	304 stainless steel
	Outer tube pressure	35MPa (continuous)/70MPa (peak) or 350bar ( continuous)/700bar (peak)
	Position magnet	Standard magnet ring and various ring magnets
RP Series	Electronic bin	Aluminum alloy
	Measuring rod	Aluminum alloy
	Position magnet	Slider magnet, square magnet, sector magnet
Mounting thread form		M18×1.5、 M20×1.5、 3/4"-16UNF-3A (customizable)
Installation direction		Any direction
Outgoing mode		Cable outlet or Connector

### • Electrical Connection


Input voltage	+24Vdc $\pm 20\%$
operating current	$<90\text{mA}$ (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	$>10\text{M}\Omega$
Insulation strength	500V

## A a Installation Instructions-EtherCAT Output

### • Dimensions and installation guidance of RH pressure-resistant rod sensor


RH series pressure-resistant rodshell, built-in installation design for hydraulic system, pressure-resistant 35MPa continuous, flexible and simple installation mode. Mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.

Note: The measurement Non-usable area shown in the figure indicates that the output value of the sensor in this area is zero or unreliable. The default values of the first and last measurement Non-usable areas of this product are 50.8mm and 63.5mm respectively. The value of the measurement Non-usable area can be appropriately modified according to the needs of customers, please pointed out when ordering.













### • Dimensions and installation guidance of RP aluminum profile sensor




RP Series aluminum profile provides flexible and simple external installation mode, which is suitable for stroke or position detection of linear motion mechanism, and can also be used for external position detection of hydraulic cylinder.



## Common Accessories-EtherCAT Output

Accessory name/ model		Dimensions	
Female Connector (for power supply) Order No. : 522000-xx (xx- cable length, unit m)		Industrial Ethernet Cable (Cat 5e) d-coded Order No. : 522005-xx (xx- cable length, unit m)	 Connector type: RJ45, 4-pin 90° male connector (M12) Cable sheath: PVC, light blue working temperature:-40 C ~80 C
4-pin90° female connector (for power supply) Order No. : 522001-xx (xx- cable length, unit m)		Industrial Ethernet Cable (Cat 5e) d-coded Order No. : 522006-xx (xx- cable length, unit m)	 Connector Type: RJ45, 4-pin straight male connector (M12) Cable sheath: PVC, light blue Working temperature:-40 C ~80 C
Industrial Ethernet Cable (Cat 5e) d-coded Order No. : 522004-xx (xx- cable length, unit m)	 Connector type: two 4-pin 90° male connectors (M12) Cable sheath: PVC, light blue operating temperature:-40 C ~80 C	Industrial Ethernet Cable (Cat 5e) d-coded Order No. : 522008-xx (xx- cable length, unit m)	 Connector type: Two straight male connectors (M12) Cable sheath: PVC, light blue Working temperature:-40 C ~80 C

Accessory name/ model		Dimensions	
Standard magnet ring Order No. : 211501		Sector magnet Order No. : 211502	
Slider magnet Order No. : 211503		Square magnet Order No. : 211508	

Accessory name/ model		Dimensions	
Magnetic isolation gasket		Sector magnetic isolation gasket	
4-pin male connector Order No. : 312723			

**Note:** Please refer to "Magnet ring Selection" and "Cable Selection" for details of cables, magnet rings and other models.

### • Wiring mode



4-pin connector socket  
(for power supply)

#### • Connector Connection Mode (Interface 1, 2)

Pin	Line color	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -

#### • Single cable outlet connection mode

Pin	Line color 1*	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -
5	Red	24Vdc
6	Black	COM

**Note:** \* Line color 1: light green, PUR sheath, 6 cores,-40C~85 C

#### • Connector Connection Mode (Interface 3)

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc (-20%~+20%)
2	White	Do not connect
3	Blue	COM
4	Black	Do not connect

#### • Double cable outlet connection mode

Pin	Line color1*	Line color2*	Pin/wire function definition
1	Yellow	Yellow	Tx +
2	White	White	Rx +
3	Orange	Orange	Tx -
4	Blue	Blue	Rx -
5	Red	-	24Vdc
6	Black	-	COM

**Note:** \* Line color 2: light green, PUR sheath, 4 cores,-40C~70 C



## X Selection Guide-EtherCAT Output

R  - M     -    -      - E    -     

01 02     03 04 05 06 07     08 09     10 11 12 13     14 15 16 17     18 19 20 21

01 - 02		Sensor shell form
R	H	Pressure-resistant rod (internal or external)
R	P	Aluminum profile (external only)

03 - 07		Measuring range
		Four digits, less than four digits are preceded by zero, M means metric system, unitmm

08 - 09		Magnet ring type/mounting thread form
Only for RH series	S 1	M18×1.5, measuring rod diameter 10mm, 304 material
	S 2	M20×1.5, measuring rod diameter 10mm, 304 material
	S 3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material
	T 1	M18×1.5, measuring rod diameter 8mm, 304 material
	T 2	M20×1.5, measuring rod diameter 8mm, 304 material
	T 3	3/4"-16UNF-3A, measuring rod diameter 8mm, 304 material
Only for RP Series	C 1	Sector magnet
	C 2	Slider magnet
	C 3	Square magnet

10 - 13		Connection form
D	A * *	Single cable outlet, light green, PUR sheath (6 cores)
D	B * *	Double cable outlet, light green, PUR sheath (one set of 6 cores, one set of 4 cores)
P	D 5 6	2 sets of 4-pin M12 female connectors, 1 set of 4-pin M8 male connector
		Note: * * Indicates the length of cable in meters

14 - 17		Communication interface
14 - 15		Sensor form
E	1	EtherCAT, position and speed, distributed clock optional
16 - 17		Number of magnet rings
		01~09 optional
18 - 19		Non-usable area at head and end, customizable
S	0	50.8mm+63.5mm
B	0	30mm+60mm
S	1	28mm+66mm (used in RP series)
20-21		Country
		Refer to the country list, page 130.


● Selection example: RH-M0300-S1 -PD56-E101-S0

Indicates: RH structure series, 300mm Stroke length, M18X1.5 mounting thread, measuring rod diameter 10mm, 304 material, 2 sets of 4-pin female connectors, M12, 1 set of 4-pin male connector, M8, Profinet protocol, single magnet ring, head Non-usable area 50.8mm, end Non-usable area 63.5mm.

## L LED real-time state monitoring and diagnosis

- Red and green LEDs built into the sensor head cover provide sensor working condition and diagnostic function.

Green light	Flash	×
Red light	OFF	ON
Function	Normal work	Magnets not detected or incorrect number




# RF Flexible Outer Tube Displacement Sensor



## Technical Characteristics

- Suitable for long-stroke cylinder applications
- Easy to diagnose, LED indicator status indication
- Not limited by installation space
- Non-wear, non-contact measurement method
- Rugged and fully enclosed design
- Linear measurement, absolute value output
- Curly packaging saves space, packaging and transportation costs
- Direct displacement output: Analog, SSI, Profibus-DP, CANopen, Start/Stop, Profinet, EtherCAT



## Product Parameters

### • Input

Measurement data	Position magnet ring
Stroke length	500~7620mm, customized according to customer needs, Up to 23 meters
Number of measurements	Multiple, depending on the output interface

### • Output

Interface	Analog、SSI、Profibus-DP、CANopen、Start/Stop、Profinet、EtherCAT
Resolution	Depending on the output
Nonlinearity	$<\pm 0.01\%$ of full scale, minimum $\pm 50\mu\text{m}$
Repetition accuracy	$<\pm 0.001\%$ of full scale, min. $1\mu\text{m}$
Hysteresis	$< 10\mu\text{m}$
Update time	1KHz (range $\leq 1\text{m}$ )    500Hz ( $1\text{m} < \text{range} \leq 2\text{m}$ ) 250Hz ( $2\text{m} < \text{range} \leq 3\text{m}$ ), customizable
Temperature coefficient	$< 30\text{ppm}/^\circ\text{C}$

### • Operating conditions

Magnet velocity	Arbitrary
Protection level	IP65 (When combined with pressure-resistant outer tube, the protection level can reach IP67)
Operating temperature	$-40^\circ\text{C} \sim +85^\circ\text{C}$ (up to $105^\circ\text{C}$ )
Humidity/dew point	Humidity 90%, no condensation
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC Test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Electrical connection



Input voltage	$+24\text{Vdc} \pm 20\%$
operating current	$< 90\text{mA}$ (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	$> 10\text{M}\Omega$
Insulation strength	500V

### • Structure and materials

Failure indication	Electronic bin cover with LEDs display
Electronic bin	Aluminum alloy
Measuring rod	Stainless steel hose, minimum bending radius 250mm, shipping radius 400mm
Position magnet	Standard magnet ring and various ring magnets
Installation direction	Any direction
Outgoing mode	Cable outlet or Connector

## A a Installation and Use Instructions

### • Dimensions of RF flexible outer tube sensor





**Option:** Pressure-resistant outer pipe with flange, outer diameter 12mm/12.7mm

The flanged pressure-resistant outer pipe is used to cooperate with RF flexible sensor, which can withstand 35MPa pressure for hydraulic cylinder and provide protection for RF sensor. For large Cylinder, it is necessary to drill a  $\phi 18$ mm deep hole in the piston rod when selecting the pressure pipe with 12mm outer diameter, which can match our magnet ring with large inner diameter.



### • Installation instruction of RF flexible outer tube sensor

Two non-magnetic bolts are required for the installation of the sensor electronic bin. Long-stroke sensors need non-magnetic tube support (inner diameter  $\geq 9.4$ ), or bend into the desired shape. Sensors with hexagonal flanges can be easily mounted using non-magnetic bolts. Or you can choose a flanged pressure-resistant outer pipe with an outer diameter of 12mm, with a maximum stroke of 7620mm.

#### Linear measurement (external installation)



#### Arc measurement (external installation)



**X x Selection Guide-Analog Quantity**

R F - M     -   -     -     -   -

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21

01 - 02	Sensor shell form
<span>R</span> <span>F</span>	Hose shell

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unitmm

08 - 09	Magnet ring type/mounting thread form
<span>C</span> <span>1</span>	Without flange
<span>C</span> <span>2</span>	With flange M18×1.5
<span>C</span> <span>3</span>	With flange M20×1.5
<span>C</span> <span>4</span>	With flange 3/4"-16UNF-3A

10 - 13	Connection form
---------	-----------------

10 - 11	Cable outlet mode
---------	-------------------

<span>D</span> <span>H</span>	PUR sheath, orange,-20~90℃, end scattered, line color 1
<span>D</span> <span>U</span>	PVC sheath, orange,-20~105℃, end scattered, line color 2
<span>D</span> <span>B</span>	PVC sheath, orange,-20~105℃, end scattered, line color 3
<span>D</span> <span>I</span>	PUR sheath, orange,-20~90℃, end with 6-pin connector
<span>D</span> <span>V</span>	PVC sheath, orange,-20~105℃, end with 6-pin connector
<span>D</span> <span>C</span>	PVC sheath, orange,-20~105℃, end with 8-pin connector

12 - 13	Cable length, 01~99 units: meters (Cable outlet mode)
---------	---

10 - 13	Connector mode
---------	----------------

<span>P</span> <span>H</span> <span>6</span> <span>0</span>	M16 male connector (6-pin)
<span>P</span> <span>B</span> <span>8</span> <span>0</span>	M16 male connector (8-pin)

**Note:** For supporting cables, please refer to Analog/Start-Stop Cable Accessories Selection Guide

14 - 17	Signal output mode
---------	--------------------

14 - 15	Output form and direction
---------	---------------------------

<span>A</span> <span>0</span>	Current output, 4 ~ 20mA
<span>A</span> <span>1</span>	Current output, 20 ~ 4mA
<span>A</span> <span>2</span>	Current output, 0 ~ 20mA
<span>A</span> <span>3</span>	Current output, 20 ~ 0mA
<span>V</span> <span>0</span>	Voltage output, 0 ~ 10V
<span>V</span> <span>1</span>	Voltage output, 10 ~ 0V
<span>V</span> <span>2</span>	Voltage output, -10 ~ +10V
<span>V</span> <span>3</span>	Voltage output, +10 ~ -10V
<span>V</span> <span>4</span>	Voltage output, 0 ~ 5V
<span>V</span> <span>5</span>	Voltage output, 5 ~ 0V
<span>V</span> <span>6</span>	Voltage output, -5 ~ +5V
<span>V</span> <span>7</span>	Voltage output, +5 ~ -5V

16	Number of magnet rings
----	------------------------

<span>1</span>	Single magnet ring
----------------	--------------------

17	No magnet ring state
----	----------------------

<span>A</span>	Keep the original value
<span>B</span>	Maximum value
<span>C</span>	Minimum value

18 - 19	Non-usable area at head and end, customizable
---------	---

<span>S</span> <span>0</span>	50.8mm+63.5mm
<span>S</span> <span>9</span>	50.8mm+107mm
<span>S</span> <span>B</span>	61mm+94mm

20-21	Country
-------	---------

<span></span> <span></span>	Refer to the country list, page 130.
-----------------------------	--------------------------------------

● Description: RF regular stroke is 500~7620mm, if you need longer stroke, please call our company to customize.

● Selection example:RF-M6000-C1-PH60-A01C-S0

Indicates: the installation mode of the ordered product is built-in RF flexible structure, the stroke length is 6000m, six pin connector, 4-20A output, the output value of non-magnet ring is the minimum value, the single magnet ring, without connecting flange, the non-usable area at the head is 50.8mm, and the non-usable area at the end is 63.5mm.

## X Selection Guide-SSI

RF - M -  -  - S -

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23

01 - 02	Sensor shell form
<span>R</span> <span>F</span>	Hose shell

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unitmm

08 - 09	Magnet ring type/mounting thread form
<span>C</span> <span>1</span>	Without flanges
<span>C</span> <span>2</span>	With flange M18×1.5
<span>C</span> <span>3</span>	With flange M20×1.5
<span>C</span> <span>4</span>	With flange 3/4"-16UNF-3A

10 - 13	Connection form
---------	-----------------

10 - 11	Cable outlet mode
<span>D</span> <span>H</span>	PUR sheath, orange,-20~90℃, end scattered, line color 1
<span>D</span> <span>U</span>	PVC sheath, orange,-20~105℃, end scattered, line color 2
<span>D</span> <span>B</span>	PVC sheath, orange,-20~105℃, end scattered, line color 3
<span>D</span> <span>I</span>	PUR sheath, orange,-20~90℃, end with 7-pin connector
<span>D</span> <span>V</span>	PVC sheath, orange,-20~105℃, end with 7-pin connector
<span>D</span> <span>C</span>	PVC sheath, orange,-20~105℃, end with 8-pin connector

12 - 13	Cable outlet mode: cable length, 01 ~99 meters
---------	--

10 - 13	Connector mode
---------	----------------

<span>P</span> <span>H</span> <span>7</span> <span>0</span>	M16 male connector (7 pins)
<span>P</span> <span>B</span> <span>8</span> <span>0</span>	M16 male connector (8-pin)

14 - 19	Signal output mode
---------	--------------------

15	Data length
----	-------------

<span>1</span>	24bit	<span>2</span>	25bit	<span>3</span>	26bit*
* 26-bit are parity bits and 25-bit are status bits					

16	Data format
----	-------------

<span>B</span>	Binary	<span>G</span>	Gray code
----------------	--------	----------------	-----------

17	Resolution
----	------------

<span>1</span>	0.1mm	<span>2</span>	0.05mm
<span>3</span>	0.02mm	<span>4</span>	0.01mm
<span>5</span>	0.005mm	<span>6</span>	0.002mm
<span>7</span>	0.001mm	<span>8</span>	0.04mm
<span>9</span>	0.0005mm	<span>0</span>	0.0001mm

18	Direction
----	-----------

<span>0</span>	Forward	<span>1</span>	Reverse
----------------	---------	----------------	---------

19	Mode
----	------

<span>0</span>	Regular	<span>1</span>	Synchronization	<span>2</span>	High update rate
----------------	---------	----------------	-----------------	----------------	------------------

20 - 21	Non-usable area at head and end, customizable
---------	---

<span>S</span> <span>0</span>	50.8mm+63.5mm
<span>S</span> <span>9</span>	50.8mm+107mm

22-23	Country
-------	---------

<span></span> <span></span>	Refer to the country list, page 130.
-----------------------------	--------------------------------------

**Note:** For supporting cables, please refer to SS Cable Accessories Selection Guide

**X x Selection Guide-Profibus-DP**

R	F	-	M					-	C		-					-	D			-			-		
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16		17	18		19	20

01 - 02	Sensor shell form
R F	Hose shell

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Magnet ring type/mounting thread form
C 1	Without flange
C 2	With flange M18×1.5
C 3	With flange M20×1.5
C 4	With flange 3/4"-16UNF-3A

10 - 13	Connection form
---------	-----------------

10 - 11	Cable outlet mode
D A	Single cable outlet, PUR sheath, cyan,-20~80℃, end scattered
D B	Double cable outlet, PUR sheath, cyan,-20~80℃, end scattered
D C	Double cable outlet, PUR sheath, cyan,-20~80℃, end M16, 6-core, one male connector, one female connector

12 - 13	Cable outlet mode: cable length, 01~99 meters
---------	---

10 - 13	Connector mode
P D 5 3	One set of 5-pin male connector (M12), one set of 5-pin female connector (M12), one set of 4-pin male connector (M8)
P D 6 3	A set of 6-pin male connector (M16), a set of 6-pin female connector (M16)

14 - 16	Signal output mode
14	Profibus Protocol
15	Number of Magnet rings (1~9 optional)
16	0-single magnet B-single/multiple Magnet rings

17 - 18	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
S 9	50.8mm+107mm

19-20	Country
	Refer to the country list, page 130.

**Note:** For supporting cables, please refer to Profibus-DP Cable Accessories Selection Guide

## X Selection Guide-CAN Bus

R	F	-	M					-			-					-	C					-			-		
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16	17	18		19	20		21	22

01 - 02	Sensor shell form
R F	Hose shell

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Magnet ring type/mounting thread form
C 1	Without flange
C 2	With flange M18×1.5
C 3	With flange M20×1.5
C 4	With flange 3/4"-16UNF-3A

10 - 13	Connection form
10 - 11	Cable outlet mode
D A	PVC sheath, purple, 4 cores, -40℃~75℃, end scattered

12 - 13	Cable outlet mode: cable length, 01~99meters
0 D R 1	PVC sheath, length 150mm, end 5-pin male connector

10 - 13	Connector mode
P D 6 0	6-pin male connector (M16)
P D 6 2	Two sets of 6-pin male connector (M16)
P D 5 0	5-pin male connector (M12)
P D 5 2	5-pin male connector (M12), one set of 5-pin female connector (M12)
P D 5 4	5-pin male connector (M12), 5-pin female connector (M12), 4-pin male connector (M8)

**Note:** For supporting cables, please refer to CAN bus cable Accessories selection

14 - 18	Signal output mode
14	Interface
C	CAN bus

15	Protocol type
1	CANopen
2	CANBasic

16	Baud
1	1000kBit/s
2	800kBit/s
3	500kBit/s
4	250kBit/s
5	125kBit/s
6	100kBit/s
7	50kBit/s
8	20kBit/s

17	Resolution
1	0.1mm
2	0.05mm
3	0.02mm
4	0.01mm
5	0.005mm
6	0.002mm
7	0.001mm

18	Number of Magnet rings ( 1~9 optional)
----	--

19 - 20	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
S 9	50.8mm+107mm

21-22	Country
	Refer to the country list, page 130.



**X x Selection Guide-Profinet Output**

<b>R</b>	<b>F</b>	—	<b>M</b>					—			—					—	<b>N</b>			—			—		
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16		17	18		19	20

<b>01 - 02</b>	<b>Sensor shell form</b>
<b>R</b> <b>F</b>	Hose shell

<b>03 - 07</b>	<b>Measuring range</b>
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

<b>08 - 09</b>	<b>Magnet ring type/mounting thread form</b>
<b>C</b> <b>1</b>	Without flange
<b>C</b> <b>2</b>	With flange M18×1.5
<b>C</b> <b>3</b>	With flange M20×1.5
<b>C</b> <b>4</b>	With flange 3/4"-16UNF-3A

<b>10 - 13</b>	<b>Connection form</b>
<b>D</b> <b>A</b> <b>*</b> <b>*</b>	Single cable outlet, light green, PUR sheath (6 cores), -40℃~85℃ (cable length, unit: meters)
<b>D</b> <b>B</b> <b>*</b> <b>*</b>	Double cable outlet, light green, PUR sheath (one set of 6 cores, 40℃~85℃; one set of 4 cores, -40℃~70℃) (cable length, unit: meters)
<b>P</b> <b>D</b> <b>5</b> <b>6</b>	2 sets of 4-pin female connector, M12, 1 set of 4-pin male connector, M8

**Note:** For supporting cables, please refer to the Guide for Selection of Industrial Ethernet Cable Accessories

<b>14 - 16</b>	<b>Communication interface</b>
<b>14</b> <b>N</b>	Profinet communication interface
<b>15</b>	Number of Magnet rings (1~9 optional)
<b>16</b>	0-General, customizable

<b>17 - 18</b>	<b>Non-usable area at head and end, customizable</b>
<b>S</b> <b>0</b>	50.8mm+63.5mm
<b>S</b> <b>9</b>	50.8mm+107mm

<b>19-20</b>	<b>Country</b>
	Refer to the country list, page 130.



**X x Selection Guide-Start/Stop Output**

R F - M - - - - - R - - - - -  
01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21

01 - 02	Sensor shell form	10 - 13	Cable outlet mode
R F	Hose shell	10 - 13	0 D R cable outlet first and end with plastic connector
03 - 07	Measuring range	0 D R 2	Scattered wire with plastic connector 65mm
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm	0 D R 3	Scattered wire with plastic connector 170mm
08 - 09	Magnet ring type/mounting thread form	0 D R 4	Scattered wire with plastic connector 230mm
C 1	Without flange	0 D R 5	Scattered wire with plastic connector 350mm
C 2	With flange M18×1.5	10 - 13	Connector mode
C 3	With flange M20×1.5	P H 6 0	M16 male connector (6 pins)
C 4	With flange 3/4"-16UNF-3A	Note: For supporting cables, please refer to the Guide for Selection of Cable Accessories	
10 - 13	Connection form	14 - 17	Signal output mode
10 - 11	Cable outlet mode	15	Input voltage
D H	PUR sheath, orange, -20~90℃, end scattered, cable color 1	1	+ 24Vdc ( - 20% ~ + 20% )
D U	PVC sheath, orange, -20~105℃, end scattered, cable color 2	2	+ 9 ~ 28.8Vdc
D B	PVC sheath, orange, -20~105℃, end scattered, cable color 3	16 - 17	Output signal
D I	PUR sheath, orange, -20~90℃, end 6-pin connector	0 1	Start/Stop, multi-Magnet ring
D V	PVC sheath, orange, -20~105℃, end 6-pin connector	18 - 19	Non-usable area at head and end, customizable
D C	PVC sheath, orange, -20~105℃, end 8-pin connector	S 0	50.8mm+63.5mm
12 - 13	Cable length, 01~99 units: meters (Cable outlet mode)	S 9	50.8mm+107mm
		20-21	Country
			Refer to the country list, page 130.

**X x Selection Guide-Pressure Outer Tube**

F - S - M - - - - -  
01 02 03 04 05 06 07 08 09 10 11

01 - 02	RF flange measuring rod
F A	Flange measuring rod, measuring rod outer diameter 12mm
F B	Flange measuring rod, measuring rod outer diameter 12.7 mm
F C	Flange measuring rod, measuring rod outer diameter 10mm
03 - 04	Flange thread specification
S 1	M18×1.5
S 2	M20×1.5
S 3	3/4"-16UNF-3A
05 - 09	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm
10 - 11	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
S 9	50.8mm+107mm

## J J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### Analogue



#### • Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	Blue	Grey	No.1 Magnet position signal(+)
2	Green	Pink	Position signal of No.1 Magnet(-)
3	Yellow	Yellow	Reservation
4	White	Green	Reservation
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc (power supply circuit)

**Note:** \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### Analogue



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Current output
2	Grey	0Vdc(Current/Voltage Loop)
3	Pink	Reservation
4	-	Reservation
5	Green	0...10V
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

### SSI



#### • Pin arrangement of seven-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	White	Grey	Data (-)
2	Yellow	Pink	Data (+)
3	Blue	Yellow	Clock (+)
4	Green	Green	Clock (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc
7	-	-	Do not connect

**Note:** \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### SSI




#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Clock (+)
2	Grey	Data (+)
3	Pink	Clock (-)
4	-	Reservation
5	Green	Data (-)
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

## J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode



• Pin arrangement of four-pin male connector (facing the sensor head)


Pin	Cable color	Pin/wire function definition
1	Brown	+24Vdc power supply (-20%~+20%)
2	White	Do not connect
3	Blue	0Vdc(power supply circuit)
4	Black	Do not connect



• Five-pin male connector and female connector pin arrangement (facing the sensor head direction)

Pin	Cable color	Pin/wire function definition
1	-	VP+5N (for end connections only) *
2	Green	RxD/TxD-N(bus)
3	-	DGnd (for end connections only) *
4	Red	RxD/TxD-P(bus)
5	Shielded wire	for end connections only


Note: \* Only applicable to signal connection of sensor female connector



• The pins of the six-pin male connector and female connector are arranged in the direction of the sensor head


Pin	Cable color	Pin/wire function definition
1	Green	RxD/TxD-N(bus)
2	Red	RxD/TxD-P(bus)
3	-	DGnd (for end connections only) *
4	-	VP+5N (for end connections only) *
5	Black	+24Vdc power supply (-20%~+20%)
6	Blue	0 Vdc (power supply circuit)

Note: \* Only applicable to signal connection of sensor female connector



• Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Green	CAN (-)
2	Yellow	CAN (+)
3	-	Do not connect
4	-	Do not connect
5	Brown	+24Vdc power supply (-20%~+20%)
6	White	0 Vdc (power supply circuit)



• Five-pin male connector and female connector pin arrangement (facing the sensor head direction)

Pin	Cable color	Pin/wire function definition
1	-	Do not connect
2	Brown	+24 Vdc power supply (-20%~+20%)
3	White	0Vdc (power supply circuit)
4	Yellow	CAN (+)
5	Green	CAN (-)



Four-pin connector socket (for power supply)

• Pin arrangement of four-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Brown	+24 Vdc power supply(-20%~+20%)
2	White	Do not connect
3	Blue	0Vdc(power supply circuit)
4	Black	Do not connect

## J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### Profinet Output



#### • Connector Connection Mode (Interface 1, 2)

Pin	Line color	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -

#### • Single cable outlet connection mode

Pin	Line color 1*	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -
5	Red	24Vdc
6	Black	COM

**Note:** \* Line color 1: light green, PUR sheath, 6 cores, -40C~85 C

### Profinet Output



4-pin connector socket  
(for power supply)

#### • Connector Connection Mode (Interface 3)

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc (-20%~+20%)
2	White	Do not connect
3	Blue	COM
4	Black	Do not connect

#### • Double cable outlet connection mode

Pin	Line color1*	Line color2*	Pin/wire function definition
1	Yellow	Yellow	Tx +
2	White	White	Rx +
3	Orange	Orange	Tx -
4	Blue	Blue	Rx -
5	Red	-	24Vdc
6	Black	-	COM

**Note:** \* Line color 2: light green, PUR sheath, 4 cores, -40C~70 C

### Start/Stop Output



#### • 6-pin male connector arrangement (facing the sensor head)

Pin	Line color 1*	Line color 2*	Pin/wire function definition
1	Blue	Grey	Stop (-)
2	Green	Pink	Stop (+)
3	Yellow	Yellow	Start (+)
4	White	Green	Start (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc

**Note:** \* Line color 1: Cable PUR sheath, orange, -20~90 C  
\* Line color 2/3: Cable PVC sheath, orange, -20~105 C

## J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### EtherCAT Output



#### • Connector Connection Mode (Interface 1, 2)

Pin	Line color	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -

#### • Single cable outlet connection mode

Line color 1*	Pin/wire function definition
Yellow	Tx +
White	Rx +
Orange	Tx -
Blue	Rx -
Red	24Vdc
Black	COM

**Note:** \* Line color 1: light green, PUR sheath, 6 cores, -40C~85℃

### EtherCAT Output



4-pin connector socket  
(for power supply)

#### • Connector Connection Mode (Interface 3)

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc (-20%~+20%)
2	White	Do not connect
3	Blue	COM
4	Black	Do not connect

#### • Double cable outlet connection mode

Line color1*	Line color2*	Pin/wire function definition
Yellow	Yellow	Tx +
White	White	Rx +
Orange	Orange	Tx -
Blue	Blue	Rx -
Red	-	24Vdc
Black	-	COM

**Note:** \* Line color 2: light green, PUR sheath, 4 cores, -40C~70℃

# RD Split Displacement Sensor



## Technical Characteristics

- Rugged and fully enclosed design
- Non-wear, non-contact measurement method
- Linear measurement, absolute output
- Sealing grade up to IP68
- Low power consumption design effectively reduces system heating
- Ultra-high temperature sensing rod (up to + 125 °C)
- Multiple interfaces available: Analog, SSI, Profibus-DP, CANopen, Start-Stop, Profinet, EtherCAT



## C Product Parameters

### • Input

Measurement data	Position Magnet ring
Stroke length	25mm~5500mm, customized according to customer needs

### • Output

Interface	Analog、SSI、CANopen、Profibus-DP、Start-Stop、Profinet、EtherCAT
Resolution	Analog: 16-bit D/A or 0.0015% of full scale (min. 1μm) Bital: 0.5 / 1 / 2 / 5 / 10 / 20 / 40 / 50 / 100 μm
Nonlinearity	< ± 0.01% of full scale, Min. ± 50μm
Repetition accuracy	< 0.001% for full-scale taxis, Min. ± 1μm
Hysteresis	< 10μm
Update time	1KHz (range≤1m)    500Hz (1m<range≤2m) 250Hz (2m<range≤3m) , customizable
Temperature coefficient	< 30ppm/℃

### • Working conditions

Magnet ring velocity	Arbitrary
Protection level	IP68 (Sensor Lever)
Operating temperature	Sensor rod -40℃ ~ +125℃ , electronic bin-40℃ ~ +85℃
Humidity/dew point	100%, relative humidity
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Electrical connection

Input voltage	+24Vdc±20%
operating current	< 100mA (varying with range)
Polarity protection	Max.-30Vdc
Overpressure protection	Max.36Vdc
Insulation resistance	> 10MΩ
Insulation strength	500V

### • Structure and materials



Fault indication	Electronic bin cover with LEDs display
Electronic bin	Aluminum alloy
Measuring rod	304 stainless steel
Outer tube pressure	35MPa (continuous)/70MPa (peak) or 350bar (continuous)/700bar (peak)
Position magnet	Standard Magnet ring and various magnet rings
Mounting thread form	M18×1.5 (customizable)
Installation direction	Any direction
Cable outlet mode	Cable outlet cable or connector

## A a Installation and Use Instructions


### • Output characteristic

RD Series sensors are designed in a split form and are suitable for installation in cylinder, especially for cylinder applications in confined spaces. The sensor consists of two parts: a sensing rod and an electronic bin. The sensor rod is a pressure-resistant stainless round pipe with threads or flanges to provide protection for the sensing elements, and the whole sensor rod is installed in the cylinder through pistons. The temperature resistance of the sensing rod up to + 125 °C, and the protection level reaches IP68, which is very suitable for harsh occasions such as high temperature, high humidity and water vapor; The electronic bin encapsulates the sensor signal processing part and the external interface together, reaching IP67 protection level, and can be connected with the sensor rod through the side or bottom of the connector plate.


### • RD Split Sensor Installing Dimensions



• Flange A metric thread M18×1.5 hexagon flange 46




• Flange B metric thread M18×1.5



• Flange C connecting flange

## A a Installation and Use Instructions

### • RDSplit Sensor Installing Dimensions





**X x Selection Guide-SSI**

R	D	-	M					-		-					-	S							-			-					
01	02		03	04	05	06	07		08		09	10	11		12	13	14	15		16	17	18	19	20	21		22	23		24	25

01 - 02	Sensor shell form
R D	Split structure

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08	Outer tube flange
A	M18X1.5 SW46
B	M18X1.5 SW24
C	Connecting flange

09 - 11	Connection mode of outer tube
09	Cable outlet mode
S	Cable enters from the side, PUR cable
B	Cable entry from bottom, independent cable with flat plastic connector
C	Cable entry from side, independent cable with flat plastic connector

10 - 11			Cable length							
M	1	1m		M	2	2m		M	3	3m
M	4	1.5m		D	1	250mm		D	2	400mm
D	3	600mm		R	2	65mm		R	4	170mm
R	5	230mm		R	6	350mm				

12 - 15	Connection form
12 - 13	Cable outlet mode
D H	PUR sheath, orange,-20~90℃, end scattered, cable color 1
D U	PVC sheath, orange,-20~105℃, end scattered, cable color 2
D B	PVC sheath, orange,-20~105℃, end scattered, cable color 3
D I	PUR sheath, orange,-20~90℃, end 7-pin connector
D V	PVC sheath, orange,-20~105℃, end 7-pin connector
D C	PVC sheath, orange,-20~105℃, end 8-pin connector

14 - 15	Cable outlet mode: cable length, 01~99 meters
---------	---

12 - 15	Connector mode
---------	----------------

P H 7 0	M16 male connector (7 pins)
---------	-----------------------------

P B 8 0	M16 male connector (8 pins)
---------	-----------------------------

**Note:** For supporting cables, please refer to SSI cable accessories selection guide

16 - 21	Signal output mode
---------	--------------------

17	Data length
----	-------------

1	24bit	2	25bit	3	26bit*
---	-------	---	-------	---	--------

\* 26-bit are parity bits and 25-bit are status bits

18	Data format
----	-------------

B	Binary	G	Gray code
---	--------	---	-----------

19	Resolution
----	------------

1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm	8	0.04mm
9	0.0005mm	0	0.0001mm

20	Direction
----	-----------

0	Forward	1	Reverse
---	---------	---	---------

21	Mode
----	------

0	Regular	1	Synchronization	2	High update rate
---	---------	---	-----------------	---	------------------

22 - 23	Non-usable area at head and end, customizable
---------	---

S 0	50.8mm+63.5mm
-----	---------------

B 0	30mm+60mm
-----	-----------

24-25	Country
-------	---------

	Refer to the country list, page 130.
--	--------------------------------------

## X Selection Guide-Profibus-DP Bus

R D - M     -  -    -     - D  -   -

01   02   03   04   05   06   07   08   09   10   11   12   13   14   15   16   17   18   19   20   21   22

01 - 02	Sensor shell form
<span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;">D</span>	Split structure

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08	Outer tube flange
<span style="border: 1px solid black; padding: 2px;">A</span>	M18X1.5 SW46
<span style="border: 1px solid black; padding: 2px;">B</span>	M18X1.5 SW24
<span style="border: 1px solid black; padding: 2px;">C</span>	Connecting flange

09 - 11	Connection mode of outer tube
09	Cable outlet mode
<span style="border: 1px solid black; padding: 2px;">S</span>	Cable enters from the side, PUR cable
<span style="border: 1px solid black; padding: 2px;">B</span>	Cable entry from bottom, independent cable with flat plastic connector
<span style="border: 1px solid black; padding: 2px;">C</span>	Cable entry from side, independent cable with flat plastic connector

10 - 11			Cable length					
M	1	1m	M	2	2m	M	3	3m
M	4	1.5m	D	1	250mm	D	2	400mm
D	3	600mm	R	2	65mm	R	4	170mm
R	5	230mm	R	6	350mm			

12 - 15	Connection form
12 - 13	Cable outlet mode
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">A</span>	Single cable outlet, PUR sheath, cyan,-20-80℃, end scattered
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">B</span>	Double cable outlet, PUR sheath, cyan,-20~80℃, end scattered
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">C</span>	Double cable outlet, PUR sheath, cyan,-20~80℃, end M16, 6-pin, one male connector, one female connector
14 - 15	Cable outlet mode: cable length, 01-99m

12 - 15	Connector mode
<span style="border: 1px solid black; padding: 2px;">P</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">5</span> <span style="border: 1px solid black; padding: 2px;">3</span>	One set of 5-pin male connector (M12), one set of 5-pin female connector (M12), one set of 4-pin male connector (M8)
<span style="border: 1px solid black; padding: 2px;">P</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">6</span> <span style="border: 1px solid black; padding: 2px;">3</span>	A set of 6-pin male connector M16 and a set of 6-pin female connector M16
	<b>Note:</b> Please refer to Profibus-DP cable fitting selection for supporting cables

16 - 18	Signal output mode
<span style="border: 1px solid black; padding: 2px;">16</span>	Profibus Protocol
<span style="border: 1px solid black; padding: 2px;">17</span>	Number of Magnet rings (1~9 optional)
<span style="border: 1px solid black; padding: 2px;">18</span>	0-single magnet    B-single/multiple Magnet rings

19 - 20	Non-usable area at head and end, customizable
<span style="border: 1px solid black; padding: 2px;">S</span> <span style="border: 1px solid black; padding: 2px;">0</span>	50.8mm+63.5mm
<span style="border: 1px solid black; padding: 2px;">B</span> <span style="border: 1px solid black; padding: 2px;">0</span>	30mm+60mm

21-22	Country
<span style="border: 1px solid black; padding: 2px;"></span> <span style="border: 1px solid black; padding: 2px;"></span>	Refer to the country list, page 130.

**X x Selection Guide-Start/Stop Output**

01 02 - 03 04 05 06 07 - 08 - 09 10 11 - 12 13 14 15 - 16 17 18 19 - 20 21 - 22 23

01 - 02	Sensor shell form
R D	Split structure

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08	Outer tube flange
A	M18X1.5 SW46
B	M18X1.5 SW24
C	Connecting flange

09 - 11	Connection mode of outer tube
09	Cable outlet mode
S	Cable enters from the side, PUR cable
B	Cable entry from bottom, independent cable with flat plastic connector
C	Cable entry from side, independent cable with flat plastic connector

10 - 11			Cable length							
M	1	1m		M	2	2m		M	3	3m
M	4	1.5m		D	1	250mm		D	2	400mm
D	3	600mm		R	2	65mm		R	4	170mm
R	5	230mm		R	6	350mm				

12 - 15	Connection form
12 - 13	Cable outlet mode
D H	PUR sheath, orange,-20~90℃, end scattered, cable color 1
D U	PVC sheath, orange,-20~105℃, end scattered, cable color 2
D B	PVC sheath, orange,-20~105℃, end scattered, cable color 3
D I	PUR sheath, orange,-20~90℃, end 6-pin connector
D V	PVC sheath, orange,-20~105℃, end 6-pin connector
D C	PVC sheath, orange,-20~105℃, end 8-pin connector
14 - 15	Cable length, 0199 units: meters (Cable outlet mode)

12 - 15	Cable outlet mode
12 - 15	0 D R cable outlet first and end with plastic connector

0 D R 2	Scattered wire with plastic connector 65mm
0 D R 3	Scattered wire with plastic connector 170mm
0 D R 4	Scattered wire with plastic connector 230mm
0 D R 5	Scattered wire with plastic connector 350mm

12 - 15	Connector mode
P H 6 0	M16 male connector (6 pins)

**Note:** For supporting cables, please refer to the Guide for Selection of Cable Accessories

16 - 19	Signal output mode
17	Input voltage
1	+ 24Vdc ( - 20% ~ + 20% )
2	+ 9 ~ 28.8Vdc
18 - 19	Output signal
0 1	Start/Stop, multi-Magnet ring

20 - 21	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
S 9	50.8mm+107mm

22-23	Country
	Refer to the country list, page 130.

## X Selection Guide-CAN Bus

R D - M - - - - - C - - - - - - - - - -

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24

01 - 02	Sensor shell form
R D	Split structure

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08	Outer tube flange
A	M18X1.5 SW46
B	M18X1.5 SW24
C	Connecting flange

09 - 11	Connection mode of outer tube
---------	-------------------------------

09	Cable outlet mode
S	Cable enters from the side, PUR cable
B	Cable entry from bottom, independent cable with flat plastic connector
C	Cable entry from side, independent cable with flat plastic connector

10 - 11	Cable length
---------	--------------

M 1	1m	M 2	2m	M 3	3m
M 4	1.5m	D 1	250mm	D 2	400mm
D 3	600mm	R 2	65mm	R 4	170mm
R 5	230mm	R 6	350mm		

12 - 15	Connection form
---------	-----------------

12 - 13	Cable outlet mode
D A	PVC sheath, purple, 4 cores, -40℃~75℃, end scattered

14 - 15	Cable outlet mode: cable length, 01-99m
---------	---

0 D R 1	PVC sheath, length 150mm, end 5-pin male connector
---------	--

12 - 15	Connector mode
---------	----------------

P D 6 0	6-pin male connector (M16)
P D 6 2	Two sets of 6-pin male connector (M16)
P D 5 0	5-pin male connector (M12)
P D 5 2	5-pin male connector (M12) and 5-pin female connector (M12)
P D 5 4	5-pin male connector (M12), 5-pin female connector (M12), 4-pin male connector (M8)

**Note:** For supporting cables, please refer to CAN bus cable Accessories selection

16 - 20	Signal output mode
16	Interface

C CAN bus

17	Protocol type
----	---------------

1 CANopen 2 CANBasic

18	Baud
----	------

1	1000kBit/s	2	800kBit/s
3	500kBit/s	4	250kBit/s
5	125kBit/s	6	100kBit/s
7	50kBit/s	8	20kBit/s

19	Resolution
----	------------

1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm		

20	Number of Magnet rings (1~9 optional)
----	---------------------------------------

21 - 22	Non-usable area at head and end, customizable
---------	---

S 0 50.8mm+63.5mm  
B 0 30mm+60mm

23-24	Country
-------	---------

Refer to the country list, page 130.



**X x Selection Guide-Profinet Output**

R	D	-	M					-		-					-	N			-			-						
01	02		03	04	05	06	07		08		09	10	11		12	13	14	15		16	17	18		19	20		21	22

01 - 02	Sensor shell form
R D	Split structure

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08	Outer tube flange
A	M18X1.5 SW46
B	M18X1.5 SW24
C	Connecting flange

09 - 11	Connection mode of outer tube
---------	-------------------------------

09	Cable outlet mode
S	Cable enters from the side, PUR cable
B	Cable entry from bottom, independent cable with flat plastic connector
C	Cable entry from side, independent cable with flat plastic connector

10 - 11		Cable length						
M	1	1m	M	2	2m	M	3	3m
M	4	1.5m	D	1	250mm	D	2	400mm
D	3	600mm	R	2	65mm	R	4	170mm
R	5	230mm	R	6	350mm			

12 - 15	Connection form
D A * *	Single cable outlet, light green, PUR sheath (6 cores), -40℃~85℃ (* * indicating cable length, unit: meter)
D B * *	Double cable outlet, light green, PUR sheath (one set of 6 cores, -40℃~85℃; one set of 4 cores, -40℃~70℃) (* * denotes cable length, unit: meters)
P D 5 6	2 sets of 4-pin M12 female connector, 1 set of 4-pin M8 male connector

**Note:** For supporting cables, please refer to the Guide for Selection of Industrial Ethernet Cable Accessories

16 - 18	Communication interface
16 N	Profinet communication interface
17	Number of Magnet rings (1~9 optional)
18	0-General, customizable

19 - 20	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
S 9	50.8mm+107mm

21-22	Country
	Refer to the country list, page 130.

## X Selection Guide-EtherCAT Output



01 - 02	Sensor shell form
R D	Split structure

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08	Outer tube flange
A	M18X1.5 SW46
B	M18X1.5 SW24
C	Connecting flange

09 - 11	Connection mode of outer tube
09	Cable outlet mode
S	Cable enters from the side, PUR cable
B	Cable entry from bottom, independent cable with flat plastic connector
C	Cable entry from side, independent cable with flat plastic connector

10 - 11			Cable length									
M	1	1m			M	2	2m			M	3	3m
M	4	1.5m			D	1	250mm			D	2	400mm
D	3	600mm			R	2	65mm			R	4	170mm
R	5	230mm			R	6	350mm					

12 - 15	Connection form
D A * *	Single cable outlet, light green, PUR sheath (6 cores), -40°C~85°C ( * * indicating cable length, unit: meter)
D B * *	Double cable outlet, light green, PUR sheath (one set of 6 cores, -40°C~85°C; one set of 4 cores, -40°C~70°C) ( * * denotes cable length, unit: meters)
P D 5 6	2 sets of 4-pin M12 female connector, 1 set of 4-pin M8 male connector

16 - 19	Communication interface
16 - 17	Sensor form
E 1	EtherCAT, 1-9 magnets, position and speed, distributed clock optional
18 - 19	Number of Magnet rings
	01~09 optional

20 - 21	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
B 0	30mm+60mm

22-23	Country
	Refer to the country list, page 130.

## J J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### Analog



#### • Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	Blue	Grey	No.1 Magnet position signal(+)
2	Green	Pink	Position signal of No.1 Magnet(-)
3	Yellow	Yellow	Reservation
4	White	Green	Reservation
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc (power supply circuit)

**Note:** \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### Analog



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Current output
2	Grey	0Vdc(Current/Voltage Loop)
3	Pink	Reservation
4	-	Reservation
5	Green	0...10V
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

### SSI



#### • Pin arrangement of seven-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	White	Grey	Data (-)
2	Yellow	Pink	Data (+)
3	Blue	Yellow	Clock (+)
4	Green	Green	Clock (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc
7	-	-	Do not connect

**Note:** \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### SSI



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Clock (+)
2	Grey	Data (+)
3	Pink	Clock (-)
4	-	Reservation
5	Green	Data (-)
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

### Start/Stop Output



#### • 6-pin male connector arrangement (facing the sensor head)

Pin	Line color 1*	Line color 2*	Pin/wire function definition
1	Blue	Grey	Stop (-)
2	Green	Pink	Stop (+)
3	Yellow	Yellow	Start (+)
4	White	Green	Start (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc(power supply circuit)

**Note:** \* Line color 1: Cable PUR sheath, orange, -20~90 °C  
\* Line color 2/3: Cable PVC sheath, orange, -20~105 °C

### Start/Stop Output




#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Line color 1*	Pin/wire function definition
1	Yellow	Start (+)
2	Grey	Stop (+)
3	Pink	Start (-)
4	-	Reservation
5	Green	Stop (-)
6	Blue	0 Vdc(power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation


## J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode



### • Pin arrangement of four-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Brown	+24Vdc power supply (-20%~+20%)
2	White	Do not connect
3	Blue	0Vdc(power supply circuit)
4	Black	Do not connect



### • Five-pin male connector and female connector pin arrangement (facing the sensor head direction)

Pin	Cable color	Pin/wire function definition
1	-	VP+5N (for end connections only) *
2	Green	RxD/TxD-N(bus)
3	-	DGnd (for end connections only) *
4	Red	RxD/TxD-P(bus)
5	Shielded wire	for end connections only

Note: \* Only applicable to signal connection of sensor female connector



### • The pins of the six-pin male connector and female connector are arranged in the direction of the sensor head

Pin	Cable color	Pin/wire function definition
1	Green	RxD/TxD-N(bus)
2	Red	RxD/TxD-P(bus)
3	-	DGnd (for end connections only) *
4	-	VP+5N (for end connections only) *
5	Black	+24Vdc power supply (-20%~+20%)
6	Blue	0 Vdc (power supply circuit)

Note: \* Only applicable to signal connection of sensor female connector




### • Connector Connection Mode (Interface 1, 2)

Pin	Line color	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -

### • Single cable outlet connection mode

Pin	Line color 1*	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -
5	Red	24Vdc
6	Black	COM

Note: \* Line color 1: light green, PUR sheath, 6 cores, -40C~85 C



### • Connector Connection Mode (Interface 3)

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc (-20%~+20%)
2	White	Do not connect
3	Blue	COM
4	Black	Do not connect

### • Double cable outlet connection mode

Pin	Line color1*	Line color2*	Pin/wire function definition
1	Yellow	Yellow	Tx +
2	White	White	Rx +
3	Orange	Orange	Tx -
4	Blue	Blue	Rx -
5	Red	-	24Vdc
6	Black	-	COM


Note: \* Line color 2: light green, PUR sheath, 4 cores, -40C~70 C

## Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### CAN bus output


Four-pin connector socket  
(for power supply)



#### • Pin arrangement of four-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Brown	+24Vdc power supply (-20%~+20%)
2	White	Do not connect
3	Blue	0Vdc(power supply circuit)
4	Black	Do not connect

### CAN bus output



#### • Five-pin male connector and female connector pin arrangement (facing the sensor head direction)

Pin	Cable color	Pin/wire function definition
1	-	Do not connect
2	Brown	+24Vdc power supply (-20%~+20%)
3	White	0Vdc (power supply circuit)
4	Yellow	CAN (+)
5	Green	CAN (-)

### CAN bus output



#### • Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Green	CAN (-)
2	Yellow	CAN (+)
3	-	Do not connect
4	-	Do not connect
5	Brown	+24Vdc power supply (-20%~+20%)
6	White	0 Vdc (power supply circuit)

### EtherCAT Output



#### • Connector Connection Mode (Interface 1, 2)


Pin	Line color	Pin/wire function definition
1	Yellow	Tx +
2	White	Rx +
3	Orange	Tx -
4	Blue	Rx -

#### • Single cable outlet connection mode

Line color 1*	Pin/wire function definition
Yellow	Tx +
White	Rx +
Orange	Tx -
Blue	Rx -
Red	24Vdc
Black	COM

**Note:** \* Line color 1: light green, PUR sheath, 6 cores, -40C~85℃

### EtherCAT Output



4-pin connector socket  
(for power supply)

#### • Connector Connection Mode (Interface 3)

Pin	Line color	Pin/wire function definition
1	Brown	+24Vdc (-20%~+20%)
2	White	Do not connect
3	Blue	COM
4	Black	Do not connect

#### • Double cable outlet connection mode

Line color1*	Line color2*	Pin/wire function definition
Yellow	Yellow	Tx +
White	White	Rx +
Orange	Orange	Tx -
Blue	Blue	Rx -
Red	-	24Vdc
Black	-	COM

**Note:** \* Line color 2: light green, PUR sheath, 4 cores, -40C~70℃

# RS Waterproof Displacement Sensor



## Technical Characteristics

- Non-wear, non-contact measurement method Rugged and
- fully enclosed design
- Linear measurement, absolute position output Low power
- consumption design effectively reduces system heating
- Sealing grade up to IP67
- Multiple signal type optional: Analog, SSI, CANopen, Start/Stop



## Product Parameters

### • Input

Measurement data	Position Magnet ring
Stroke length	50mm~5500mm, customized according to customer's needs
Number of measurements	1

### • Output

Interface	Analog、SSI、CANopen、Start/Stop
Resolution	Analog: 16-bit D/A or 0.0015% of full scale (min. 1μm) Bital quantity: 0.5 / 1 / 2 / 5 / 10 / 20 / 40 / 50 / 100 μm
Nonlinearity	< ± 0.01% of full scale, Min. ±50μm
Repetition accuracy	< ± 0.001% of full scale, Min. ± 1μm
Hysteresis	< 10μm
Update time	1KHz (range ≤ 1m)      500Hz (1m < range ≤ 2m) 250Hz (2m < range ≤ 3m), customizable
Temperature coefficient	< 30ppm/℃

### • Working conditions

Magnet ring velocity	Arbitrary
Protection level	IP68
Operating temperature	-40℃ ~ +105℃
Humidity/dew point	Humidity 100%, relative humidity
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Electrical connection

Input voltage	Normal: +24Vdc ± 20% Wide voltage: 9Vdc ~ 28.8Vdc
operating current	< 90mA (varying with range)
Polarity protection	Max. -30Vdc
Overpressure protection	Max. 36Vdc
Insulation resistance	> 10MΩ
Insulation strength	500V

### • Structure and materials


Electronic bin	304 stainless steel, or 316L according to customer requirements
Measuring rod	304 stainless steel, or 316L according to customer requirements
Outer tube pressure	35MPa (continuous)/70MPa (peak) or 350bar (continuous)/700bar (peak)
Position magnet	Standard Magnet ring and various magnet rings
Mounting thread form	M18×1.5、M20×1.5、3/4"-16UNF-3A (customizable)
Installation direction	Any direction
Cable outlet mode	Cable outlet

## A a Installation and Use Instructions

### • Output characteristic


RS series sensors have strong protective shell, which is durable and can provide users with continuous, reliable and real-time displacement signals in harsh environment. The sensor is completely sealed with stainless steel shell, which fully meets the protection level IP68. Note: The electronic compartment is not detachable.

Because of the non-contact measurement technology, the sensor can be integrated in an isolated and sealed shell. The position magnet moves along the measuring rod, and the position can be measured without mechanical contact. For liquid level measurement, an alternative float can be used. The sensor with high protection level shell is easy to install and use, so as to better meet the application requirements. The measurement accuracy and all technical parameters depend on the output characteristics of the selected sensor, and the interface form can be selected: analog or SSI.



### • Installation dimensions of RS waterproof sensor

RS Series super protective Sensor, designed for cylinder built-in installation in harsh environment, withstands pressure of 35MPa for continuous, flexible and simple installation mode, and mounting thread form M18×1.5 or M20×1.5 or 3/4"-16UNF-3A.



**Note:** It is equipped with standard Magnet ring kit 288501, with magnetic isolation gasket and fixing screw.

## C c Commonly Used Accessories

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard Magnet ring Order No.: 211501		Magnet ring Order No.: 211506		Enlarge magnet ring Order No.: 211504	
Magnet ring Order No.: 211507					

• **Note:** Please refer to "Magnet ring Selection" for details of Magnet ring kit and other models



**X x Selection Guide-Analog**

**R** **S** - **M**     - **S**  - **D**     -     -   -

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21

01 - 02	Sensor shell form
<b>R</b> <b>S</b>	Pressure-resistant pipe

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Magnet ring type/mounting thread form
<b>S</b> <b>1</b>	M 18×1.5, measuring rod diameter 10mm, 304 material
<b>S</b> <b>2</b>	M20×1.5, measuring rod diameter 10mm, 304 material
<b>S</b> <b>3</b>	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material

10 - 13	Connection form
---------	-----------------

10 - 11	Cable outlet mode
<b>D</b> <b>H</b>	PUR sheath, orange, -20~90℃, end scattered, cable color 1
<b>D</b> <b>U</b>	PVC sheath, orange, -20~105℃, end scattered, cable color 2
<b>D</b> <b>B</b>	PVC sheath, orange, -20~105℃, end scattered, cable color 3
<b>D</b> <b>I</b>	PUR sheath, orange, -20~90℃, end 6-pin connector
<b>D</b> <b>V</b>	PVC sheath, orange, -20~105℃, end 6-pin connector
<b>D</b> <b>C</b>	PVC sheath, orange, -20~105℃, end 8-pin connector

12 - 13	Cable outlet mode: cable length, 01~99 meters
---------	---

10 - 13	Connector mode
---------	----------------

<b>P</b> <b>H</b> <b>6</b> <b>0</b>	M16 male connector (6 pins)
<b>P</b> <b>B</b> <b>8</b> <b>0</b>	M16 male connector (8 pins)

**Note:** For supporting cables, please refer to Analog/Start-Stop Cable Accessories Selection

14 - 17	Signal output mode
---------	--------------------

14 - 15	Output form and direction
<b>A</b> <b>0</b>	Current output, 4 ~ 20mA
<b>A</b> <b>1</b>	Current output, 20 ~ 4mA
<b>A</b> <b>2</b>	Current output, 0 ~ 20mA
<b>A</b> <b>3</b>	Current output, 20 ~ 0mA
<b>V</b> <b>0</b>	Voltage output, 0 ~ 10V
<b>V</b> <b>1</b>	Voltage output, 10 ~ 0V
<b>V</b> <b>2</b>	Voltage output, -10 ~ +10V
<b>V</b> <b>3</b>	Voltage output, +10 ~ -10V
<b>V</b> <b>4</b>	Voltage output, 0 ~ 5V
<b>V</b> <b>5</b>	Voltage output, 5 ~ 0V
<b>V</b> <b>6</b>	Voltage output, -5 ~ +5V
<b>V</b> <b>7</b>	Voltage output, +5 ~ -5V

16	Number of magnet ring
----	-----------------------

<b>1</b>	Single magnet ring
----------	--------------------

17	No magnet ring state
----	----------------------

<b>A</b>	Keep the original value
<b>B</b>	Max. value
<b>C</b>	Min. value

18 - 19	Non-usable area at head and end, customizable
---------	---

<b>S</b> <b>0</b>	50.8mm+63.5mm
<b>B</b> <b>0</b>	30mm+60mm

20-21	Country
-------	---------

<input type="text"/> <input type="text"/>	Refer to the country list, page 130.
---	--------------------------------------

- **Note:** The forward output of the sensor means that when the Magnet ring moves away from the electronic bin, the output value increases and decreases when the Magnet ring moves in the reverse direction.

- **Selection examples:** RS-M0300-S1-DU02-V01B-S0

Indicates: the installation mode of the ordered product is built-in waterproof steel structure, the stroke length is 300mm, the thread is M18×1.5, the measuring rod diameter is 10mm, the material is 304, cable outlet, cable length is 2 meters (PVC sheath, orange, -20~105℃, the end is scattered), the output is 0-10V, the output value of No Magnet ring is the Max., and the single Magnet ring is forward

## X Selection Guide-SSI

R	S	-	M					-			-					-	S							-			-		
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16	17	18	19		20	21		22	23	

01 - 02	Sensor shell form
R S	Pressure-resistant pipe

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Magnet ring type/mounting thread form
S 1	M 18×1.5, measuring rod diameter 10mm, 304 material
S 2	M20×1.5, measuring rod diameter 10mm, 304 material
S 3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material

10 - 13	Connection form
10 - 11	Cable outlet mode
D H	PUR sheath, orange, -20~90℃, end scattered, cable color 1
D U	PVC sheath, orange, -20~105℃, end scattered, cable color 2
D B	PVC sheath, orange, -20~105℃, end scattered, cable color 3
D I	PUR sheath, orange, -20~90℃, end 6-pin connector
D V	PVC sheath, orange, -20~105℃, end 6-pin connector
D C	PVC sheath, orange, -20~105℃, end 8-pin connector

12 - 13	Cable outlet mode: cable length, 01 ~99 meters
10 - 13	Connector mode
P H 7 0	M16 male connector (7 pins)
P B 8 0	M16 male connector (8 pins)

**Note:** For supporting cables, please refer to the Guide for Selection of Cable Accessories

14 - 19	Signal output mode
15	Data length

1	24bit	2	25bit	3	26bit *
* 26-bit are parity bits and 25-bit are status bits					

16	Data format			
	B	Binary	G	Gray code

17	Resolution		
1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm	8	0.04mm
9	0.0005mm	0	0.0001mm

18	Direction	
0	Forward	1 Reverse

19	Mode				
0	Regular	1	Synchronization	2	High update rate

20 - 21	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
B 0	30mm+60mm

22-23	Country
	Refer to the country list, page 130.

**X x Selection Guide-CAN Bus**

**R** **S** - **M**     -   -     - **C**     -   -

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22

01 - 02	Sensor shell form
<input type="text"/> <input type="text"/>	Pressure-resistant pipe

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Magnet ring type/mounting thread form
<input type="text"/> <input type="text"/>	M18×1.5, measuring rod diameter 10mm, 304 material
<input type="text"/> <input type="text"/>	M20×1.5, measuring rod diameter 10mm, 304 material
<input type="text"/> <input type="text"/>	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material

10 - 13	Connection form
---------	-----------------

10 - 11	Cable outlet mode
<input type="text"/> <input type="text"/>	PVC sheath, purple, 4 cores, -40℃~75℃, end scattered

12 - 13	Cable outlet mode: cable length, 01~99 meters
<input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>	PVC sheath, length 150mm, end 5-pin male connector

10 - 13	Connector mode
<input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>	Set of 6-pin male connector (M16)

**Note:** For supporting cables, please refer to CAN bus cable Accessories selection

14 - 18	Signal output mode
<input type="text"/>	Interface
<input type="text"/>	CAN bus

15	Protocol type
<input type="text"/>	CANopen
<input type="text"/>	CANBasic

16	Baud
<input type="text"/>	1000kBit/s
<input type="text"/>	800kBit/s
<input type="text"/>	500kBit/s
<input type="text"/>	250kBit/s
<input type="text"/>	125kBit/s
<input type="text"/>	100kBit/s
<input type="text"/>	50kBit/s
<input type="text"/>	20kBit/s

17	Resolution
<input type="text"/>	0.1mm
<input type="text"/>	0.05mm
<input type="text"/>	0.02mm
<input type="text"/>	0.01mm
<input type="text"/>	0.005mm
<input type="text"/>	0.002mm
<input type="text"/>	0.001mm

18	Number of Magnet rings (1~9 optional)
----	---------------------------------------

19 - 20	Non-usable area at head and end, customizable
<input type="text"/> <input type="text"/>	50.8mm+63.5mm
<input type="text"/> <input type="text"/>	30mm+60mm

21-22	Country
<input type="text"/> <input type="text"/>	Refer to the country list, page 130.

## X Selection Guide-Start/Stop Output

R S - M     -   -     - R    -   -

01 02      03 04 05 06 07      08 09      10 11 12 13      14 15 16 17      18 19      20 21

01 - 02	Sensor shell form
<span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;">S</span>	Pressure-resistant pipe

03 - 07	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Magnet ring type/mounting thread form
<span style="border: 1px solid black; padding: 2px;">S</span> <span style="border: 1px solid black; padding: 2px;">1</span>	M18×1.5, measuring rod diameter 10mm, 304 material
<span style="border: 1px solid black; padding: 2px;">S</span> <span style="border: 1px solid black; padding: 2px;">2</span>	M20×1.5, measuring rod diameter 10mm, 304 material
<span style="border: 1px solid black; padding: 2px;">S</span> <span style="border: 1px solid black; padding: 2px;">3</span>	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material

10 - 13	Connection form
10 - 11	Cable outlet mode
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">H</span>	PUR sheath, orange, -20~90℃, end scattered, cable color 1
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">U</span>	PVC sheath, orange, -20~105℃, end scattered, cable color 2
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">B</span>	PVC sheath, orange, -20~105℃, end scattered, cable color 3
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">I</span>	PUR sheath, orange, -20~90℃, end 6-pin connector
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">V</span>	PVC sheath, orange, -20~105℃, end 6-pin connector
<span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">C</span>	PVC sheath, orange, -20~105℃, end 8-pin connector
12 - 13	Cable length, 01~99 units: m, (Cable outlet mode)

10 - 13	Cable outlet mode
<span style="border: 1px solid black; padding: 2px;">10</span> <span style="border: 1px solid black; padding: 2px;">13</span> <span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;"></span>	cable outlet first and end with plastic connector

<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;">2</span>	Scattered wire with plastic connector 65 mm
<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;">3</span>	Scattered wire with plastic connector 170 mm
<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;">4</span>	Scattered wire with plastic connector 230 mm
<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">D</span> <span style="border: 1px solid black; padding: 2px;">R</span> <span style="border: 1px solid black; padding: 2px;">5</span>	Scattered wire with plastic connector 350 mm

10 - 13	Connector mode
<span style="border: 1px solid black; padding: 2px;">P</span> <span style="border: 1px solid black; padding: 2px;">H</span> <span style="border: 1px solid black; padding: 2px;">6</span> <span style="border: 1px solid black; padding: 2px;">0</span>	M16 male connector (6 pins)

**Note:** For supporting cables, please refer to Analog/Start-stop Cable Accessories Selection

14 - 17	Signal output mode
15	Input voltage
<span style="border: 1px solid black; padding: 2px;">1</span>	+ 24Vdc ( - 20% ~ + 20% )
<span style="border: 1px solid black; padding: 2px;">2</span>	+ 9 ~ 28.8Vdc
16 - 17	Output signal
<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">1</span>	Start/Stop, multi-Magnet

18 - 19	Non-usable area at head and end, customizable
<span style="border: 1px solid black; padding: 2px;">S</span> <span style="border: 1px solid black; padding: 2px;">0</span>	50.8mm+63.5mm
<span style="border: 1px solid black; padding: 2px;">B</span> <span style="border: 1px solid black; padding: 2px;">0</span>	30mm+60mm

20-21	Country
<span style="border: 1px solid black; padding: 2px;"></span> <span style="border: 1px solid black; padding: 2px;"></span>	Refer to the country list, page 130.

## J J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### Analogue



#### • Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	Blue	Grey	No.1 Magnet position signal(+)
2	Green	Pink	Position signal of No.1 Magnet(-)
3	Yellow	Yellow	Reservation
4	White	Green	Reservation
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc (power supply circuit)

Note: \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### Analogue



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Current output
2	Grey	0Vdc(Current/Voltage Loop)
3	Pink	Reservation
4	-	Reservation
5	Green	0...10V
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

### SSI



#### • Pin arrangement of seven-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	White	Grey	Data (-)
2	Yellow	Pink	Data (+)
3	Blue	Yellow	Clock (+)
4	Green	Green	Clock (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc
7	-	-	Do not connect

Note: \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### SSI



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Clock (+)
2	Grey	Data (+)
3	Pink	Clock (-)
4	-	Reservation
5	Green	Data (-)
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

## J J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode



Start/Stop Output

- 6-pin male connector arrangement (facing the sensor head)

Pin	Line color 1*	Line color 2*	Pin/wire function definition
1	Blue	Grey	Stop (-)
2	Green	Pink	Stop (+)
3	Yellow	Yellow	Start (+)
4	White	Green	Start (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc(power supply circuit)

**Note:** \* Line color 1: Cable PUR sheath, orange,-20~90 °C  
 \* Line color 2/3: Cable PVC sheath, orange,-20~105 °C



Start/Stop Output

- Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Line color 1*	Pin/wire function definition
1	Yellow	Start (+)
2	Grey	Stop (+)
3	Pink	Start (-)
4	-	Reservation
5	Green	Stop (-)
6	Blue	0 Vdc(power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation



CAN bus output

- Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Green	CAN (-)
2	Yellow	CAN (+)
3	-	Do not connect
4	-	Do not connect
5	Brown	+24Vdc power supply (-20%~+20%)
6	White	0 Vdc (power supply circuit)

# RB Flat Displacement Sensor

---



## Technical Characteristics

---

- Non-wear, non-contact measurement method
- Rugged and fully enclosed design
- Linear measurement, absolute position output
- Low power consumption design effectively reduces system heating
- Sealing grade up to IP67
- Multiple signal type optional: Analog、SSI、CANopen

## CC Product Parameters

### • Input

Measurement data	Position Magnet ring
Stroke length	50mm~5500mm, customized according to customer's needs
Number of measurements	1

### • Output

Interface	Analog、SSI、CANopen
Resolution	Analog: 16-bit D/A or 0.0015% of full scale (min. 1μm) Digital quantity: 1 / 2 / 5 / 10 / 20 / 40 / 50 / 100 μm
Nonlinearity	< ± 0.01% of full scale, Min. ± 50μm
Repetition accuracy	< ± 0.001% of full scale, Min. ± 1μm
Hysteresis	< 10μm
Update time	1KHz (range ≤ 1m)    500Hz (1m < range ≤ 2m) 250Hz (2m < range ≤ 3m), customizable
Temperature coefficient	< 30ppm/°C

### • Operating conditions

Magnet ring velocity	Arbitrary
Protection level	IP67
Operating temperature	-40 °C ~ +85 °C
Humidity/dew point	100%, relative humidity
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification

### • Electrical connection

Input voltage	+24Vdc±20%
operating current	< 100mA (varying with range)
Polarity protection	Max.-30Vdc
Overvoltage protection	Max.36Vdc
Insulation resistance	> 10MΩ
Insulation strength	500V

### • Structure and materials

Electronic bin	304 stainless steel
Measuring rod	304 stainless steel
Outer tube pressure resistance	35MPa (continuous)/70MPa (peak) or 350ba (continuous)/700ba (peak)
Position magnet	Standard magnetic ring and various ring magnets
Mounting thread	6 M6X16 screws, M18×1.5、M20×1.5 (Customizable)
Installation direction	Any direction
Connection type	Cable outlet or connector




## A a Installation and Instructions for use

### • Output characteristic


RB series sensors have high-strength protective shell and high working temperature, and are durable, which can provide users with continuous, reliable and real-time displacement signals in harsh environment. The sensor has a completely stainless steel shell. It is suitable for installing in hydraulic cylinder and measuring the stroke of piston, and is widely used in energy and mining industries. Thanks to its flat and compact design, the sensor is very suitable for cylinder installation in narrow space.

### • Installation dimensions



#### Tight pressure seal type



#### External thread type



## C c Commonly used accessories

Accessory name/ model	Dimensions	Accessory name/ model	Dimensions
Standard magnetic ring Order No.: 211501		Standard Magnet ring Kit Order No.: 288501	 Includes: 1 Magnet, 1 gasket, 4 screws with spring washer

• **Note:** Please refer to "Magnet Ring Selection" for details of magnet ring kit and other models

## X Selection Guide-Analog Quantity

$$\begin{array}{cccccccccccccccccccc} \boxed{R} & \boxed{B} & - & \boxed{M} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & - & \boxed{\phantom{0}} & \boxed{\phantom{0}} & - & \boxed{\phantom{0}} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & - & \boxed{\phantom{0}} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & \boxed{\phantom{0}} & - & \boxed{\phantom{0}} & \boxed{\phantom{0}} & - & \boxed{\phantom{0}} & \boxed{\phantom{0}} \\ 01 & 02 & & 03 & 04 & 05 & 06 & 07 & & 08 & 09 & & 10 & 11 & 12 & 13 & & 14 & 15 & 16 & 17 & & 18 & 19 & & 20 & 21 \end{array}$$

01 - 02		Sensor shell form		14 - 17		Signal output mode	
R	B	Compact sealing installation		14 - 15		Output form and direction	
03 - 07		Stroke length		A	0	Current output, 4 ~ 20mA	
		Four digits, less than four digits are preceded by zero, M means metric system, unit mm		A	1	Current output, 20 ~ 4mA	
08 - 09		Installation form		A	2	Current output, 0 ~ 20mA	
S	1	Bottom seal		A	3	Current output, 20 ~ 0mA	
S	2	Middle seal		V	0	Voltage output, 0 ~ 10V	
S	A	M18X1.5 measuring rod diameter 10mm, 304 material		V	1	Voltage output, 10 ~ 0V	
S	B	M20X1.5 measuring rod diameter 10mm, 304 material		V	2	Voltage output, -10 ~ +10V	
10 - 13		Connection form		V	3	Voltage output, +10 ~ -10V	
10 - 11		For cable outlet		V	4	Voltage output, 0 ~ 5V	
D	H	PUR sheath, orange, -20~90℃, end scattered, cable color 1		V	5	Voltage output, 5 ~ 0V	
D	U	PVC sheath, orange, -20~105℃, end scattered, cable color 2		V	6	Voltage output, -5 ~ +5V	
D	B	PVC sheath, orange, -20~105℃, end scattered, cable color 3		V	7	Voltage output, +5 ~ -5V	
D	I	PUR sheath, orange, -20~90℃, end with 6-pin connector		16		Number of magnet ring	
D	V	PVC sheath, orange, -20~105℃, end with 6-pin connector		1	Single magnet ring		
D	C	PVC sheath, orange, -20~105℃, end with 8-pin connector		17		No magnet ring state	
12 - 13		For cable outlet: cable length, 01~99 meters		A	Keep the original value		
10 - 13		For connector		B	Max. value		
P	H	6	0	C	Min. value		
P	B	8	0	18 - 19		Non-usable area at head and end, customizable	
M16 male connector (6 pins)				S	4	40mm+60mm	
M16 male connector (8 pins)				20-21		Country	
						Refer to the country list, page 130.	

**Note:** For supporting cables, please refer to Analog/Start-Stop Cable Accessories Selection

- **Note:** The forward output of the sensor means that when the magnet ring moves away from the electronic bin, the output value increases and decreases when the magnet ring moves in the reverse direction.
  - **Examples of selection:** RB-M3600-S1-PH60-A01C-S4
- Indication: The product is a compact sealed RB structure, with an effective stroke of 3600 mm, a bottom sealed M18×1.5, six-pin connector, output of 4-20 mA, Min. output value of no magnet ring state, single magnet ring, non-usable area of 40mm at the head and 60mm at the end.

**X x** Selection Guide-SSI

R	B	-	M					-			-				S					-			-					
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16	17	18	19		20	21		22	23

01 - 02	Sensor shell form
R B	Compact sealing installation

03 - 07	Stroke length
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Installation form
S 1	Bottom seal
S 2	Middle seal
S A	M18X1.5 measuring rod diameter 10mm, 304 material
S B	M20X1.5 measuring rod diameter 10mm, 304 material

10 - 13	Connection form
---------	-----------------

10 - 11	For cable outlet
D H	PUR sheath, orange, -20~90℃, end scattered, cable color 1
D U	PVC sheath, orange, -20~105℃, end scattered, cable color 2
D B	PVC sheath, orange, -20~105℃, end scattered, cable color 3
D I	PUR sheath, orange, -20~90℃, end with 7-pin connector
D V	PVC sheath, orange, -20~105℃, end with 7-pin connector
D C	PVC sheath, orange, -20~105℃, end with 8-pin connector

12 - 13	For cable outlet: cable length, 01~99 meters
---------	--

10 - 13	For connector
---------	---------------

P H 7 0	M16 male connector (7 pins)
P B 8 0	M16 male connector (8 pins)

**Note:** See SSI cable fittings selection for supporting cables

14 - 19	Signal output mode
---------	--------------------

15	Data length
----	-------------

1	24bit	2	25bit	3	26bit*
---	-------	---	-------	---	--------

\* 26-bit are parity bits and 25-bit are status bits

16	Data format
----	-------------

B	Binary	G	Gray code
---	--------	---	-----------

17	Resolution
----	------------

1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm	8	0.04mm

18	Direction
----	-----------

0	Forward	1	Reverse
---	---------	---	---------

19	Mode
----	------

0	Regular
---	---------

20 - 21	Non-usable area at head and end, customizable
---------	---

S 4	40mm+60mm
-----	-----------

22-23	Country
-------	---------

	Refer to the country list, page 130.
--	--------------------------------------

## X Selection Guide-CAN Bus

R	B	-	M					-			-					-	C					-			-			
01	02		03	04	05	06	07		08	09		10	11	12	13		14	15	16	17		18		19	20		21	22

01 - 02	Sensor shell form
R B	Compact sealing installation

03 - 07	Stroke length
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

08 - 09	Installation form
S 1	Bottom seal
S 2	Middle seal
S A	M18X1.5 measuring rod diameter 10mm, 304 material
S B	M20X1.5 measuring rod diameter 10mm, 304 material

10 - 13	Connection form
10 - 11	For cable outlet
D A	PVC sheath, purple, 4 cores, -40℃~75℃, end scattered
12 - 13	Straight-out cable mode: cable length, 01~99 meters
0 D R 1	PVC sheath, length 150mm, end with 5-pin connector
10 - 13	For connector
P D 6 0	Set of 6-pin male connectors (M16)

**Note:** For supporting cables, please refer to CAN bus cable fittings selection

14 - 18	Signal output mode
14	Interface
C	CAN bus

15	Protocol type
1	CANopen
2	CANBasic

16	Baud
1	1000kBit/s
2	800kBit/s
3	500kBit/s
4	250kBit/s
5	125kBit/s
6	100kBit/s
7	50kBit/s
8	20kBit/s

17	Resolution
1	0.1mm
2	0.05mm
3	0.02mm
4	0.01mm
5	0.005mm
6	0.002mm
7	0.001mm

18	Number of magnet rings (1~9 optional)
----	---------------------------------------

19 - 20	Non-usable area at head and end, customizable
S 4	40mm+60mm

21-22	Country
	Refer to the country list, page 130.

## J J Wiring Mode

When the sensor is a connector output, refer to the pin definition in the following table for wiring mode; when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

### Analog



#### • Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	Blue	Grey	No.1 Magnet position signal(+)
2	Green	Pink	Position signal of No.1 Magnet(-)
3	Yellow	Yellow	Reservation
4	White	Green	Reservation
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc (power supply circuit)

**Note:** \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### Analog



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Current output
2	Grey	0Vdc(Current/Voltage Loop)
3	Pink	Reservation
4	-	Reservation
5	Green	0...10V
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

### SSI



#### • Pin arrangement of seven-pin male connector (facing the sensor head)

Pin	Cable color 1*	Cable color 2*	Pin/wire function definition
1	White	Grey	Data (-)
2	Yellow	Pink	Data (+)
3	Blue	Yellow	Clock (+)
4	Green	Green	Clock (-)
5	Red	Brown	+24Vdc power supply (-20%~+20%)
6	Black	White	0 Vdc
7	-	-	Do not connect

**Note:** \* Cable color 1: Cable PUR sheath, orange, -20-90 °C  
\* Cable color 2/3: Cable PVC sheath, orange, -20-105 °C

### SSI



#### • Pin arrangement of eight-pin male connector (facing the sensor head direction)

Pin	Cable color3*	Pin/wire function definition
1	Yellow	Clock (+)
2	Grey	Data (+)
3	Pink	Clock (-)
4	-	Reservation
5	Green	Data (-)
6	Blue	0 Vdc (power supply circuit)
7	Brown	+24Vdc power supply (-20%~+20%)
8	White	Reservation

### CAN bus output



#### • Pin arrangement of six-pin male connector (facing the sensor head)

Pin	Cable color	Pin/wire function definition
1	Green	CAN (-)
2	Yellow	CAN (+)
3	-	Do not connect
4	-	Do not connect
5	Brown	+24Vdc power supply (-20%~+20%)
6	White	0 Vdc (power supply circuit)

# FBGB Explosion-Proof Displacement Sensor



## Technical Characteristics

- Non-wear, non-contact measurement method
- Rugged and fully enclosed design
- Linear measurement, absolute position output
- Low power consumption design effectively reduces system heating
- Sealing grade up to IP67
- Pressure resistance and explosion-proof, high explosion-proof grade
- Strong anti-interference performance and high reliability
- Multiple interfaces are available: Analog、SSI、CANopen

## C Product Parameters

### • Input

Measurement data	Position Magnet ring
Stroke length	25mm~5500mm, customized according to customer needs
Number of measurements	1

### • Output

Interface	Analog、SSI、CANopen
Resolution	Analog: 16-bit D/A or 0.0015% of full scale (min. 1μm) Bital quantity: 0.5 / 1 / 2 / 5 / 10 / 20 / 40 / 50 / 100 μm
Nonlinearity	< ± 0.01% of full scale, Min. ± 50μm
Repetition accuracy	< ± 0.001% of full scale, Min. ± 1μm
Hysteresis	< 10μm
Update time	1KHz (range ≤ 1m)    500Hz (1m < range ≤ 2m) 250Hz (2m < range ≤ 3m) , customizable
Temperature coefficient	< 30ppm/℃

### • Working conditions

Magnet ring velocity	Arbitrary
Protection level	IP67
Operating temperature	-40℃ ~ +85℃
Humidity/dew point	The humidity is 90, and dew cannot be condensed
Shock index	GB/T2423.5 100g(6ms)
Vibration index	GB/T2423.10 20g/10~2000Hz
EMC test	GB/T17626.2/3/4/6/8, Grade 4/3/4/3/3, Class A, CE Certification
Certified Exd II BT6	Comply with GB3836.1-2010 and GB3836.2-2010 standards Temperature range: T6 (85℃ surface)

### • Electrical Connection

Input voltage	+24Vdc±20%
operating current	< 90mA (varying with range)
Polarity protection	Max.-30Vdc
Overpressure protection	Max.36Vdc
Insulation resistance	> 10MΩ
Insulation strength	500V

### • Structure and materials

Electronic bin	304 stainless steel
Measuring rod	304/316 L stainless steel
Outer tube pressure	35MPa (continuous)/70MPa (peak) or 350ba (continuous)/700ba (peak)
Position magnet	Standard Magnet ring and various magnet rings
Mounting thread form	M18×1.5、M20×1.5、3/4"-16UNF-3A (customizable)
Installation direction	Any direction
Cable outlet mode	Special cable outlet(flameproof cable lead-in device)





## X Selection Guide-Analog Quantity

[illegible]

- Note: The forward output of the sensor means that when the Magnet ring moves away from the electronic bin, the output value increases and decreases when the Magnet ring moves in the reverse direction.

- Selection examples: FBGB-M0300-S2-DH02-A01B-B0

Indicates: the installation mode of the ordered product is built-in explosion-proof steel structure, with an stroke length of 300mm, mounting thread is M20×1.5, cable outlet, cable length is 2m (PUR sheath, orange,-20~90℃, end scattered), a 4-20mA output, a Max. output value without magnet ring, a forward output of single magnet ring, a non-usable area of 30mm at the head and a non-usable area of 60mm at the end.

## X Selection Guide-SSI

FBGB - M -  -  - S -  -

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23

01 - 04	Sensor shell form
F B G B	Explosion-proof flameproof sensor

05 - 09	Measuring range
	Four digits, less than four digits are preceded by zero, M means metric system, unit mm

10 - 11	Magnet ring type/mounting thread form
S 1	M18×1.5, measuring rod diameter 10mm, 304 material
S 2	M20×1.5, measuring rod diameter 10mm, 304 material
S 3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material

12 - 15	Connection form
---------	-----------------

12 - 13	Cable outlet mode
D H	Cable outlet, PUR sheath, orange,-20~90℃, end scattered
D U	Cable outlet, PVC sheath, orange,-20~105℃, end scattered
S H	Side outlet, PUC sheath, orange,-20~90℃, end scattered
S U	Side outlet, PVR sheath, orange,-20~105℃, end scattered

14 - 15	Cable outlet mode: cable length, 01~99 meters
---------	---

Note: See SSI cable Accessories selection for supporting cables

16 - 21	Signal output mode
17	Data length

1	24bit	2	25bit	3	26bit *
* 26-bit are parity bits and 25-bit are status bits					

18	Data format		
	B	Binary	G Gray code

19	Resolution			
1	0.1mm	2	0.05mm	
3	0.02mm	4	0.01mm	
5	0.005mm	6	0.002mm	
7	0.001mm	8	0.04mm	
9	0.0005mm	0	0.0001mm	

20	Direction			
	0	Forward	1	Reverse

21	Mode		
0	Regular	1 Synchronization	2 High update rate

22 - 23	Non-usable area at head and end, customizable
S 0	50.8mm+63.5mm
B 0	30mm+60mm

	Country
	Refer to the country list, page 130.

**X x** Selection Guide-CAN Output

F	B	G	B	-	M					-					-					-									
01	02	03	04		05	06	07	08	09		10	11		12	13	14	15		16	17	18	19	20		21	22		23	24

01 - 04		Sensor shell form		
F	B	G	B	Explosion-proof flameproof sensor

05 - 09		Measuring range
		Four digits, less than four digits are preceded by zero, M means metric system, unit mm

10 - 11		Magnet ring type/mounting thread form
S	1	M18×1.5, measuring rod diameter 10mm, 304 material
S	2	M20×1.5, measuring rod diameter 10mm, 304 material
S	3	3/4"-16UNF-3A, measuring rod diameter 10mm, 304 material

12 - 15		Connection form
12 - 13		Cable outlet mode
D	H	Cable outlet, PUR sheath, orange,-20~90℃, end scattered
D	U	Cable outlet, PVC sheath, orange,-20~105℃, end scattered
S	H	Side outlet, PUC sheath, orange,-20~90℃, end scattered
S	U	Side outlet, PVR sheath, orange,-20~105℃, end scattered

14 - 15		Cable outlet mode: cable length, 01~99 meters		
0	D	R	1	PVC sheath, length 150mm, end 5-pin male connector

**Note:** For supporting cables, please refer to CAN bus cable Accessories selection

16 - 20		Signal output mode
16		Interface
C		CAN bus

17		Protocol type	
1	CANopen	2	CANBasic

18		Baud	
1	1000kBit/s	2	800kBit/s
3	500kBit/s	4	250kBit/s
5	125kBit/s	6	100kBit/s
7	50kBit/s	8	20kBit/s

19		Resolution	
1	0.1mm	2	0.05mm
3	0.02mm	4	0.01mm
5	0.005mm	6	0.002mm
7	0.001mm		

20		Number of Magnet rings (1~9 optional)
----	--	---------------------------------------

21 - 22		Non-usable area at head and end, customizable
S	0	50.8mm+63.5mm
B	0	30mm+60mm

23-24		Country
		Refer to the country list, page 130.

## J J Wiring Mode

when the sensor is cable outlet cable output, refer to the cable color definition in the following table for connection mode

• Analog		
Cable color 1*	Cable color 2*	Pin/wire function definition
Blue	Grey	No.1 Magnet position signal(+)
Green	Pink	Position signal of No.1 Magnet(-)
Yellow	Yellow	Reservation
White	Green	Reservation
Red	Brown	+24Vdc power supply (-20%~+20%)
Black	White	0 Vdc (power supply circuit)

**Note:** \* Cable color 1: Cable PUR sheath, orange,-20-90 ℃  
 \* Cable color 2/3: Cable PVC sheath, orange,-20-105 ℃

• Analog	
Cable color3*	Pin/wire function definition
Yellow	Current output
Grey	0Vdc(Current/Voltage Loop)
Pink	Reservation
-	Reservation
Green	0...10V
Blue	0 Vdc (power supply circuit)
Brown	+24Vdc power supply (-20%~+20%)
White	Reservation

• SSI		
Cable color 1*	Cable color 2*	Pin/wire function definition
White	Grey	Data (-)
Yellow	Pink	Data (+)
Blue	Yellow	Clock (+)
Green	Green	Clock (-)
Red	Brown	+24Vdc power supply (-20%~+20%)
Black	White	0 Vdc
-	-	Do not connect


**Note:** \* Cable color 1: Cable PUR sheath, orange,-20-90 ℃  
 \* Cable color 2/3: Cable PVC sheath, orange,-20-105 ℃

• SSI	
Cable color3*	Pin/wire function definition
Yellow	Clock (+)
Grey	Data (+)
Pink	Clock (-)
-	Reservation
Green	Data (-)
Blue	0 Vdc (power supply circuit)
Brown	+24Vdc power supply (-20%~+20%)
White	Reservation

• CAN bus output	
Cable color	Pin/wire function definition
Green	CAN (-)
Yellow	CAN (+)
-	Do not connect
-	Do not connect
Brown	+24Vdc power supply (-20%~+20%)
White	0 Vdc (power supply circuit)

# Installation Instruction

## • Built-in installation instruction of RH pressure-resistant rod sensor



## • RH Pressure resistance rod sensor installation precautions

**Cylinder installing** — Pressure tube enclosed transducer (RH) usually has built-in cylinder installing, mounting thread form include: M18 x 1.5, M20 x 1.5, 3/4"-16UNF-3A. Before installation, make sure that the cylinder has been processed according to the correct size given in the atlas.

**Mechanical installation** — Sensor installation position and direction are not required, but must ensure that the installation is firm and reliable. The position magnet is installed on the moving part to be measured and keeps a proper distance from the measuring rod.


**Outdoor use** — when the sensor is used outdoors, it must be equipped with protective devices to prevent rainwater from immersing into the electronic compartment along cables or connectors in case of rain. The protective cover must consider the water outlet to prevent water accumulation.

**Position magnet** — In order to ensure the accuracy of measurement, the installing bracket of position magnet must be made of non-magnetic materials, such as screws, magnetic insulation gaskets, etc.

- Precautions: The sensor is magnetic sensitive equipment, which must keep away from the interference of external strong magnetic field. The stability and accuracy of power supply should also be considered when measuring with high precision. In use, it is also necessary to prevent the electronic bin from being impacted by foreign objects.

## • External installation guide of RH pressure-resistant rod sensor


When mounted horizontally, longer sensors (measuring ranges greater than 1m) must be mechanically supported (made of Non-magnetically permeable material).



# Installation Instruction


## • Size and Installation Guidance of RP Aluminum profile Sensor

RP Series Aluminum profile provides a flexible and simple installation. In general, the sensor can be installed on the machine surface with mounting clamps.











## • Position measurements are achieved using two types of magnets:

- 1、 The slider magnet moves along the guide rail of the aluminum profile shell, and the moving part is connected with the slider magnet through a connector bearing;
- 2、 The sector magnet is directly installed on the moving part and moves near the surface of the profile, with a gap of 3mm ( $\pm 1$ mm).
- 3、 The square magnet is directly installed on the moving part and moves near the surface of the profile, with a gap of 3mm ( $\pm 2$ mm).




# Installation Instruction

## • Type selection of pull rod



## • Selection Guide



01 Connecting thread form: F : M 5 Internal thread/D : M 5 External thread

02 - 03 Diameter of pull rod: 10, 12

04 - 08 Length of pull rod (L): Four digits, less than four digits are preceded by zero, M means metric system, unitmm

09 - 10 Mounting thread form, two choices: C1: Internal thread/C2: External thread

11 - 12 Mounting thread specification: M 5 / M 6: Tie rod diameter 1 0 m m option; M 8: Tie rod diameter 1 2 m m option

13 Whether to equip plain bearings and their locking nuts: Y: Yes/N: No

## • Selection examples:F10-L0200-C1-M5-N

Indicates: The diameter of pull rod is 10mm, the length of pull rod is 200mm, internal thread, thread specification is M5, without connector bearing.

## Gg Selection of Cable Accessories for Industrial Ethernet

NET - M -

01 02 03 04 05 06 07 08 09 10

01 - 03		Type
<span style="border: 1px solid black; padding: 2px;">N</span>	<span style="border: 1px solid black; padding: 2px;">E</span> <span style="border: 1px solid black; padding: 2px;">T</span>	Industrial Ethernet
04 - 07		Cable length
<span style="border: 1px solid black; padding: 2px;">M</span>	<span style="border: 1px solid black; padding: 2px;">*</span> <span style="border: 1px solid black; padding: 2px;">*</span> <span style="border: 1px solid black; padding: 2px;">*</span>	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10		Cable type, outlet mode
<span style="border: 1px solid black; padding: 2px;">08</span>		Cable type
<span style="border: 1px solid black; padding: 2px;">D</span>		PVC sheath, blue, 8-core, shielded, CAT-5e,-40~85℃
<span style="border: 1px solid black; padding: 2px;">A</span>		PUR sheath, green, 4-core, shielded, CAT-5e ES,-40~70℃
<span style="border: 1px solid black; padding: 2px;">09</span> <span style="border: 1px solid black; padding: 2px;">10</span>		Cable type
<span style="border: 1px solid black; padding: 2px;">1</span>	<span style="border: 1px solid black; padding: 2px;">1</span>	Two-end 4-pin male connector, M12, d-code
<span style="border: 1px solid black; padding: 2px;">2</span>	<span style="border: 1px solid black; padding: 2px;">2</span>	Two-end 4-pin right angle male connector, M12, d-code
<span style="border: 1px solid black; padding: 2px;">1</span>	<span style="border: 1px solid black; padding: 2px;">3</span>	One end 4 pin male connector, M12, d-code, one end shielded RJ 45 connector
<span style="border: 1px solid black; padding: 2px;">2</span>	<span style="border: 1px solid black; padding: 2px;">3</span>	One end 4-pin right angle male connector, M12, d-code, one end shielded RJ 45 connector

● Selection examples: NET-M010-D11

Indicates: Ethernet cable, 10m long, PVC sheathed, blue, 8-core, CAT-5e standard, shielded,-40~85℃, 4-pin male connector at both ends, M12, d-code.

## Cc Selection of SSI cable Accessories

SSI - M -

01 02 03 04 05 06 07 08 09 10

01 - 03		Type
<span style="border: 1px solid black; padding: 2px;">S</span>	<span style="border: 1px solid black; padding: 2px;">S</span> <span style="border: 1px solid black; padding: 2px;">I</span>	SSI interface
04 - 07		Cable length
<span style="border: 1px solid black; padding: 2px;">M</span>	<span style="border: 1px solid black; padding: 2px;">*</span> <span style="border: 1px solid black; padding: 2px;">*</span> <span style="border: 1px solid black; padding: 2px;">*</span>	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10		Cable type, outlet mode
<span style="border: 1px solid black; padding: 2px;">H</span>	<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">1</span>	One end of 7 pins (M16) female connector, and one end scattered
<span style="border: 1px solid black; padding: 2px;">H</span>	<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">3</span>	One end of 7 pins (M16) right angle female connector, and one end scattered
<span style="border: 1px solid black; padding: 2px;">U</span>	<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">1</span>	One end of 7 pins (M16) female connector, and one end scattered
<span style="border: 1px solid black; padding: 2px;">U</span>	<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">2</span>	One end of 8-pin (M16) female connector, and one end scattered
<span style="border: 1px solid black; padding: 2px;">U</span>	<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">3</span>	One end of 7 pins (M16) right angle female connector, and one end scattered
<span style="border: 1px solid black; padding: 2px;">U</span>	<span style="border: 1px solid black; padding: 2px;">0</span> <span style="border: 1px solid black; padding: 2px;">4</span>	One end of 8-pin (M16) right angle female connector, and one end scattered
Note		H: Cable type, PUR sheath, orange,-20~90℃
		U: Cable type, PVC sheath, orange,-20~105℃

● Selection example: SSI-M005-H01

Indicates: SSI interface cable, 5m long, PUR sheath, orange,-20~90℃, 7 pins (M16) female connector at one end, and the other end is scattered.



## D Selection of Analog/Start-Stop Cable Accessories

A S T - M - - - - -

01 02 03 04 05 06 07 08 09 10

01 - 03	Type
A S T	Analog/Start-Stop interface
04 - 07	Cable length
M * * *	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10	Cable type, outlet mode
H 0 1	One end of 6 pins (M16) female connector, and one end scattered
H 0 3	One end of 6-pin (M16) right angle female connector, and one end scattered
U 0 1	One end of 6 pins (M16) female connector, and one end scattered
U 0 2	One end of 8-pin (M16) female connector, and one end scattered
U 0 3	One end of 6-pin (M16) right angle female connector, and one end scattered
U 0 4	One end of 8-pin (M16) right angle female connector, and one end scattered
Note	H: Cable type, PUR sheath, orange, -20~90°C U: Cable type, PVC sheath, orange, -20~105°C

● Selection example: AST-M005-H01

Indicates: Analog or Start-Stop interface cable, 5m long, PUR sheath, orange, -20~90°C, 6 pins (M16) female connector at one end, and the other end is scattered.

## C Selection of CAN Bus Cable Accessories

C A N - M - - - - -

01 02 03 04 05 06 07 08 09 10

01 - 03	Type
C A N	CAN bus
04 - 07	Cable length
M * * *	Less than 3 digits are preceded by zeros, and M means metric system, unit m
08 - 10	Cable type, outlet mode
08	Cable type
C	PVC sheath, purple, 4 cores, -40~75°C
09 - 10	Cable type
0 1	One end of 6 pins (M16) female connector, and one end scattered
0 2	One end of 5-pin (M12) female connector, and one end scattered
0 3	One end of 5-pin (M12) female connector, and one end scattered
0 4	One end of 5-pin (M12) right angle female connector, and one end scattered
0 5	One end of 6-pin (M16) right angle female connector, and one end scattered
1 1	One end of 6-pin (M16) female connector
2 3	One end of 5-pin (M12) female connector; One end 5-pin (M12) male connector

● Selection example: CAN-M015-C01

Indicates: CAN bus interface cable, 15m long, PVC sheath, purple, 4 cores, -40~75°C, 6 pins (M16) female connector at one end, and the other end is scattered.

## C Selection of Profibus-DP Cable Accessories



01 - 02	Type
D P	Profibus-DP interface
03 - 06	Cable length
M * * *	Less than 3 digits are preceded by zeros, and M means metric system, unit m
07 - 09	Cable type, outlet mode
H 0 1	One end of 5-pin (M12) female connector, and one end scattered
H 0 2	One end of 5-pin (M12) male connector, and one end scattered
H 0 3	One end of 5-pin (M12) right angle female connector, and one end scattered
H 0 4	One end of 5-pin (M12) right angle male connector, and one end scattered
Z 0 5	One end of 6-pin (M16) male connector, and one end scattered
Z 0 6	One end of 6-pin (M16) male connector, and one end scattered
Z 0 7	One end of 6-pin (M16) right angle female connector, and one end scattered
H 1 2	One end of 5-pin (M12) male connector, One-end 5-pin (M12) female connector
H 3 4	One end of 5-pin (M12) right angle male connector; One-end 5-pin (M12) right angle female connector
Z 5 6	One end of 6-pin (M16) male connector; One end of 6-pin (M16) female connector
Note	H: Cable type, PUR sheath, purple, 2 cores, -20~80°C Z: Cable type, PUR sheath, cyan, 5-core, -20~80°C

- Selection example: DP-M020-H01








Indicates: Profibus-DP interface cable, 20 meters long, PUR sheath, purple, 2 cores, -20~80°C, 5-pins (M12) female connector at one end, and the other end is scattered.

- Selection example: DP-M015-Z56















Indicates: Profibus-DP interface cable, with a length of 15m, PUR sheath, cyan, 5 cores, -20~80°C, with 6 pins (M16) male connector at one end and 6 pins (M16) female connector at the other end.

















# Programming Tools Selection

Accessory name/model	Dimensions	Description
<b>Handheld programmer</b> Order No.: TEC612801A/B (A: Current B: Voltage)		Applicable to analog signal output type sensor, can set the start position and full-scale point of analog signal output type displacement sensor Includes: handheld programmer, 220V power supply, sensor adapterx2
<b>Interface converter</b> Order No.: TEC612802		Applicable to SSI signal output type sensor, bitat tube real-time display output vernier magnet ring displacement value. Includes: interface converter, 220V power supply, sensor adapterx2
<b>Address programmer</b> Order No.: TEC612803		Applicable to Profibus-DP signal output sensor, and provides the slave station address setting function of Profibus-DP signal output displacement sensor. Includes: address programmer, sensor adapter
<b>Address programmer</b> Order No.: TEC612804		Applicable to CANopen signal output sensor, and provides the slave station address setting function of CANopen signal output displacement sensor. Includes: address programmer, sensor adapter
<b>USB converter</b> Order No.: TEC612811		Applicable to analog signal output sensor, connect PC and sensor via USB port, use TEC sensor configuration software for programming: 1) setting sensor measurement direction; 2) Setting sensor zero point and full-scale point; 3) Graphical display of Magnet ring position value; 4) Diagnose sensor online through error code. Includes: USB converter, USB data cable, sensor adapterx2, software
<b>USB converter</b> Order No.: TEC612812		Applicable to SSI signal output sensor, connect PC and sensor via USB port, using TEC sensor configuration software for programming: 1) Set sensor parameters (data length, data format, measurement direction); 2) Graphic display of Magnet ring position value; 3) Set sensor zero point and measurement display value; 4) Diagnose sensor online through error code. Includes: USB converter, USB data cable, sensor adapterx2, software
<b>USB converter</b> Order No.: TEC612813		Applicable to start/stop signal output sensor, connect PC and sensor via USB port, use TEC sensor configuration software to program: 1) Graphic display of Magnet ring position value; 2) Diagnose sensor online through error code. Includes: USB converter, USB data cable, sensor adapterx2, software















# Magnet ring Selection

Accessory name/model	Dimensions	Description/application
 Standard magnet ring Order No.: 211501		Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB
 Standard magnet ring Kit Order No.: 288501		Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X18, Material 304 Spring gasket: GB/T 93, Φ 4, Material 304 Includes: 1 Magnet, 1 gasket, 4 screws with spring washer Application: RH/RF/FBGB/RS/RD/RB
 Standard magnet ring Kit Order No.: 288501-2		Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X18, Material 304 Spring gasket: GB/T 93, Φ 4, Material 304 Includes: 1 Magnet, 2 gaskets, 4 screws with spring washer Application: RH/RF/FBGB/RS/RD/RB
 Sector magnet Order No.: 211502		Includes: 1 Magnet Application: RP
 Sector magnet kit Order No.: 288502		Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X18, Material 304 Spring gasket: GB/T 93, Φ4, Material 304 Includes: 1 Magnet, 1 gasket, 2 screws with spring washer Application: RP
 Slider Magnet Order No.: 211503		Screw: M5X25, Material 304 Nut: GB/T6170, M5, Material 304 Includes: 1 slider, 1 screw, 2 nuts Application: RP
 Enlarge magnet ring Order No.: 211504		Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB















# Magnet ring Selection

Accessory name/model	Dimensions	Description/application
 <p>Enlarged magnet ring kit Order No.: 288504</p>		<p>Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X20 Spring gasket: GB/T 93, Φ4, Material 304 Includes: 1 Magnet, 1 gasket, 2 screws with spring washer Application: RH/RF/FBGB/RS/RD/RB</p>
 <p>Enlarged sector magnet Order No.: 211505</p>		<p>Includes: 1 Magnet Application: RP</p>
 <p>Enlarged sector magnet Kit Order No.: 288505</p>		<p>Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X20, Material 304 Spring gasket: GB/T 93, Φ4, Material 304 Includes: 1 Magnet, 1 gasket, 2 screws with spring washer Application: RP</p>
 <p>Magnet ring Order No.: 211506</p>		<p>Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB</p>
 <p>Magnet ring Kit Order No.: 288506</p>		<p>Magnetic insulation gasket: size same as magnet ring, thickness 5mm Retaining ring: GB/T893, 26 Includes: 1 Magnet, 2 gaskets and 1 retaining ring Application: RH/RF/FBGB/RS/RD/RB</p>
 <p>Magnet Order No.: 211507</p>		<p>Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB</p>
 <p>Magnet ring Kit Order No.: 288507</p>		<p>Magnetic insulation gasket: size same as magnet ring, thickness 5mm Retaining ring: GB/T893, 18 Includes: 1 Magnet, 2 gaskets and 1 retaining ring Application: RH/RF/FBGB/RS/RD/RB</p>

# Magnet ring Selection







Accessory name/model	Dimensions	Description/application
 Square magnet Order No.: 211508		Includes: 1 Magnet Application: RP
 Square magnet kit Order No.: 288508		Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X20, Material 304 Spring gasket: GB/T 93, $\Phi$ 4, Material 304 Includes: 1 Magnet, 1 gasket, 2 screws with spring washer Application: RP
 Magnet ring Order No.: 211509		Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB
 Magnet ring Kit Order No.: 288509		Magnetic insulation gasket: size same as Magnet ring, thickness 5mm Retaining ring: GB/T893, 18 Includes: 1 Magnet, 2 gaskets and 1 retaining ring Application: RH/RF/FBGB/RS/RD/RB
 Magnet ring 33 Order No.: 211511		Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB
 Magnet ring 33 Kit Order No.: 288511		Magnetic insulation gasket: size same as Magnet ring, thickness 5mm Screw: GB/T70.1, M4x20 Includes: 1 Magnet, 1 gasket, 2 screws with spring washer Application: RH/RF/FBGB/RS/RD/RB
 Weak magnet Magnet ring 32 Order No.: 211519		Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB

# Magnet ring Selection















Accessory name/model	Dimensions	Description/application
 <p>Weak magnet Magnet ring 32 kit Order No.: 288519</p>		<p>Magnetic insulation gasket: size same as magnet ring, thickness 5mm Screw: GB/T70.1, M4X20, Material 304 Spring gasket: GB/T93, <math>\Phi 4</math>, material 304 Includes: 1 Magnet, 1 gasket, 2 screws with spring washer Application: RH/RF/FBGB/RS/RD/RB</p>
 <p>Trapezoidal magnet Order No.: 211514</p>		<p>Includes: 1 Magnet Application: RP</p>
 <p>Trapezoidal magnet kit Order No.: 288514</p>		<p>Magnetic insulation gasket: size same as Magnet ring, thickness 5mm Screw: GB/T70.1, M4X20, Material 304 Spring gasket: GB/T93, <math>\Phi 4</math>, material 304 Includes: 1 Magnet, 1 gasket, 3 screws with spring washer Application: RP</p>
 <p>Trapezoidal Magnet (Straight) Kit Order No.: 288514A</p>		<p>Nut: GB/T6170, M5, Material 304 Includes: 1 Magnet, 1 Magnet holder, 2 screws Application: RP</p>
 <p>Trapezoidal Magnet (Bending) Kit Order No.: 288514B</p>		<p>Nut: GB/T6170, M5, Material 304 Includes: 1 Magnet, 1 Magnet holder, 2 screws Application: RP</p>
 <p>Magnet ring Order No.: 211573</p>		<p>Includes: 1 Magnet Application: RH/RF/FBGB/RS/RD/RB</p>
 <p>Magnet ring Kit Order No.: 288573</p>		<p>Nut: GB/T70.1, M4x25, Material 304 Includes: 1 Magnet, 4 screws Application: RH/RF/FBGB/RS/RD/RB</p>

















## Other Accessories

Accessory name/model	Dimensions	Description/application
 Mounting clamp kit Order No.: 211561		Nut: GB/T70.1, M5×16, Material 304 Includes: 1 clip, 2 screws Application: RP
 Mounting clamp Kit (Including Insulation washer) Order No.: 211801		Nut: GB/T70.1, M5×16, Material 304 Includes: 1 clip, 2 screws, 2 Insulation washers Application: RP
 Transfer flange kit Order No.: 988003		Nut: GB/T70.1, M5×16, Material 304 Includes: 1 flange, 6 M4×8 screws with spring washer, 1 sealing ring Application: RF/RH













# Connector Selection

Accessory name/model	Dimensions	Application
 <p>Six-pin female connector female Order No.: 312701</p>		<p>Analog Profibus-DP CAN bus Start/Stop</p>
 <p>Six-pin 90°female connector Order No.: 312702</p>		<p>Analog Profibus-DP CAN bus Start/Stop</p>
 <p>Seven-pin female connector Order No.: 312703</p>		<p>SSI</p>
 <p>Seven-pin 90°female connector Order No.: 312704</p>		<p>SSI</p>
 <p>Five-pin male end connector Order No.: 312705</p>		<p>Profibus-DP(M12)-B code</p>
 <p>Five-pin male connector Order No.: 312706</p>		<p>Profibus-DP(M12)-B code</p>
 <p>Five-pin female connector Order No.: 312707</p>		<p>Profibus-DP(M12)-B code</p>

# Connector Selection

Accessory name/model	Dimensions	Application
 Five-pin T-shape connector Order No.: 312708		Profibus-DP(M12)
 Five-pin 90° connector male head Order No.: 312709		Profibus-DP(M12)-B code
 Five-pin 90° female connector Order No.: 312710		Profibus-DP(M12)-B code
 Six-pin male connector Order No.: 312714		Profibus-DP(M16)
 Six-pin end male connector Order No.: 312715		Profibus-DP(M16)
 Seven-pin male connector Order No.: 312718		SSI
 Eight-pin female connector Order No.: 312720		SSI/Analog/Start-Stop















# Connector Selection

Accessory name/model	Dimensions	Application
 <p>Eight-pin male connector Order No.: 312721</p>		SSI/Analog/Start-Stop
 <p>Six-pin end female connector Order No.: 312722</p>		CAN bus
 <p>Four-pin male connector Order No.: 312723</p>		Industrial Ethernet /M12-D code
 <p>Eight-pin 90° female connector Order No.: 312724</p>		Analog/SSI/Start-Stop
 <p>Five-pin male connector Order No.: 312726</p>		CAN (A code)
 <p>Five-pin female connector Order No.: 312727</p>		CAN (A code)

# Cable Selection

Accessory name/model	Dimensions	Application
 Standard Cable (H) Order No.: 511802	3P×0.25mm <sup>2</sup> ; Φ7.2mm Conductor: 6-core, red/black, blue/green, yellow/white Sheath: Orange, PUR Shielding layer: tinned copper wire mesh + aluminum foil Application characteristics: soft, oil resistance and bending resistance Temperature: (-20~90℃)	Interface: Analog/SSI Interface/Start/Stop Structure: RH/RP/RF/FBGB/RS/RB/RD
 Profibus 2-Core Special Cable (H) Order No.: 511803	2×0.2mm <sup>2</sup> ; Φ8mm Conductor: 2 cores, red/green Sheath: Purple, PUR Shielding layer: tinned copper wire mesh + aluminum foil Application characteristics: Hard, special for DP Temperature: (-20~80℃)	Interface: DP interface Structure: Special for RH/RP/RF/5-pin connector
 Profibus 5-core Special Cable (Z) Order No.: 511804	1×2×0.65+3×0.75mm <sup>2</sup> ; Φ8mm Conductor: 5-core, red/green/blue/black/yellow/green Sheath: Cyan, PUR Shielding layer: tinned copper wire mesh + aluminum foil Application characteristics: Linear and soft Temperature: (-20~80℃)	Interface: DP interface Structure: Special for RH/RP/RF/6-pin connector
 Orange European Standard Cable (U) Order No.: 511807	7×0.25mm <sup>2</sup> ; Φ7mm Conductor: 7-core, white/brown/green/yellow/gray/pink/blue Sheath: Orange, modified PVC Shielding layer: tinned copper wire mesh + aluminum foil Application characteristics: Extremely soft, oil resistance, bending resistance, high temperature resistance compliant with European colour code Temperature: (-20~105℃)	Interface: Analog/SSI Interface/Start/Stop Structure: RH/RP/RF/FBGB/RS/RB/RD
 CAN Special Cable (C) Order No.: 511808	2×2×0.22mm <sup>2</sup> ; Φ7.6mm Conductor: 4-core, brown/white, yellow/green Sheath: Purple, PVC Shielding layer: braided with copper wire Application characteristics: Hard, impedance 120Ω, special for CAN Temperature: (-40~75℃)	Interface: CAN interface Structure: RH/RP/RF/FBGB/RS/RB/RD
 Black European Standard Cable (U) Order No.: 511814	7×0.25mm <sup>2</sup> ; Φ7mm Conductor: 7-core, white/brown/green/yellow/gray/pink/blue Sheath: Black, modified PVC Shielding layer: tinned copper wire mesh + aluminum foil Application characteristics: Extremely soft, oil resistance, bending resistance, high temperature resistance compliant with European colour code Temperature: (-20~105℃)	Interfaces: Analog, SSI, Start/Stop Structure: RH/RP/RF/FBGB/RS/RB/RD

# Cable Selection

Accessory name/model	Dimensions	Application
 <p>Four-pin female connector Order No.: 522000-XX</p>		<p>Profibus-DP/Profinet(M8)</p> <p>Optional: 522000-02 — line length 2m 522000-05 — line length 5m 522000-10 — line length 10m 522000-15 — Line length 15m xx- cable length unit: m</p>
 <p>Four-pin 90° female connector Order No.: 522001-XX</p>		<p>Profibus-DP/Profinet(M8)</p> <p>Optional: 522001-10 — Line length 10m 522001-15 — Line length 15m xx- cable length unit: m</p>
 <p>Wire Harness Order No.: 522003</p>		<p>Start/Stop</p>
 <p>Industrial Ethernet Cable(Cat 5e) d-coded Order No.: 522004-XX</p>		<p>Industrial Ethernet interface</p> <p>Optional: 522004-08 — Line length 8m xx- cable length unit: m</p> <p>Connector Type: Two 4-pin 90 ° male connectors (M12)</p> <p>Cable sheath: PVC, light blue</p> <p>Working temperature: -40°C ~80°C</p>
 <p>Industrial Ethernet Cable(Cat 5e) d-coded Order No.: 522005-XX</p>		<p>Industrial Ethernet interface</p> <p>Optional: 522005-08 — Line length 8m xx- cable length unit: m</p> <p>Connector type: RJ45, 4-pin 90 ° male connector(M12)</p> <p>Cable sheath: PVC, light blue</p> <p>Working temperature: -40°C ~80°C</p>
 <p>Industrial Ethernet Cable(Cat 5e) d-coded Order No.: 522006-XX</p>	 <p>Connector Type: RJ45, 4-pin male connector (M12)</p> <p>Cable sheath: PVC, light blue</p> <p>Working temperature: -40°C ~80°C</p>	<p>Industrial Ethernet interface</p> <p>Optional: 522006-03 — Line length 3m 522006-05 — Line length 5m 522006-08 — Line length 8m 522006-10 — Line length 10m 522006-15 — Line length 15m xx- cable length unit: m</p>
 <p>Industrial Ethernet Cable(Cat 5e) d-coded Order No.: 522008-XX</p>	 <p>Connector type: Two male connectors (M12)</p> <p>Cable sheath: PVC, light blue</p> <p>Working temperature: -40°C ~80°C</p>	<p>Industrial Ethernet interface</p> <p>Optional: 522008-03 — Line length 3m 522008-05 — Line length 5m 522008-08 — Line length 8m 522008-10 — Line length 10m 522008-15 — Line length 15m xx- cable length unit: m</p>

# Troubleshooting Table

## Analog

### Fault

### Reason

### Checking method

RH.RP.RD  
.RF

LEDs off	No power supply	Check whether the power supply has power. Use a multimeter to measure whether the voltage value of the power supply is normal.
	Wiring error	Check whether the sensor power cord is connected correctly
	Sensor damaged	After investigation, if it is confirmed that the sensor is damaged or faulty and needs to be returned for repair, please contact the sales staff or after-sales staff to send it back
Red and green LED keep on	No magnet /magnet mismatch/mistakenly use gasket as magnet	Test after correctly installing the magnet
	Sensor damage	After investigation, if it is confirmed that the sensor is damaged or faulty and needs to be returned for repair, please contact the sales staff or after-sales staff to send it back
The green LED is on and the red LED is flashing	The magnet leaves the stroke length range	Check whether the magnet is in the non-usable area at the head and end. Test after move the magnet or piston rod into the stroke
Green LED flashing, red LED is off	Sensor data jumping	The sensor detects that the data jump at a certain point exceeds the set threshold ( $\geq 0.5\text{mm}$ ), and needs to be returned to the factory for inspection and maintenance, please contact the sales staff or after-sales staff to send it back
LED cannot be observed, no current/voltage tested	Magnet problem in Cylinder/broken current of multimeter for test	Step 1: If the sensor is not disassembled, measure the signal cable voltage with a multimeter. About 21.6 V indicates that the sensor output is normal, and the current file of the multimeter is damaged. It is necessary to replace a new multimeter test until the current is measured Step 2: Disassemble the sensor and put on a magnet on the rod. When the green LED is on and the multimeter current/voltage value is normal, it means that the sensor is normal. If there is a problem with the magnet in the cylinder, it is necessary to disassemble the cylinder to check whether the magnet is damaged or falls off Step 3: Disassemble the sensor and put on a magnet on the rod. Moving the magnet within the stroke, if the LED is abnormal and there is no current/voltage or abnormal current/voltage value (not in the corresponding output range), please returned to the factory for detection, please contact the sales staff or after-sales staff to send it back
Displacement value does not match with Cylinder action; the deviation between reference ruler and sensor actual value is large	Parameter setting in controller (PLC) program	The stroke length parameter of the sensor in PLC program should be set with the same value as the stroke of the sensor

RS.RB.  
FBGB

The data curve increasing is stepped	The customer uses the row grounding problem of the three-wire terminal / the signal (-) needs to be connected to the ground	Connect the power ground and the signal (-) cable to the power GND terminal block / after the signal (-) cable is connected to the ground, then check whether the data returns to normal Step 1: If the sensor is not disassembled, measure the signal cable voltage with a multimeter. About 21.6 V indicates that the sensor output is normal, and the current file of the multimeter is damaged. It is necessary to replace a new multimeter test until the current is measured Step 2: After disassembled, check the appearance of the sensor and whether the cable connector is damaged. After confirming that there is no abnormality, put on a magnet to power on the sensor. If the current/voltage value of the multimeter is normal, it means that the sensor is normal, indicating that there is a problem with the magnet in the cylinder, and the cylinder needs to be disassembled to check whether the magnet is damaged or fallen off. Step 3: Disassemble the sensor and put on a magnet on the rod. Moving the magnet within the stroke, if the LED is abnormal and there is no current/voltage or abnormal current/voltage value (not in the corresponding output range), please returned to the factory for detection, please contact the sales staff or after-sales staff to send it back
Abnormal current value (current sensor) /abnormal voltage value (voltage sensor)	Problem with the magnet in the cylinder /communication module problem /The current gear of the multimeter for testing is broken /sensor damaged	

## SSI

RH.RP.RD  
.RF

LEDs are off	No power supply	After investigation, if it is confirmed that the sensor is damaged or faulty and needs to be returned for repair, please contact the sales staff or after-sales staff to send it back
	No magnet /magnet mismatch/mistakenly use gasket as magnet	Check whether the sensor power cord is connected correctly
	Sensor damage	After investigation, if it is confirmed that the sensor is damaged or faulty and needs to be returned for repair, please contact the sales staff or after-sales staff to send it back
Red and green LED keep on	No Magnet	Test after correctly installing the magnet
	Sensor damage	After investigation, if it is confirmed that the sensor is damaged or faulty and needs to be returned for repair, please contact the sales staff or after-sales staff to send it back

RH.RP.RS.  
RD.RF

Interface converter has data, but PLC shows no data	Internal fault of sensor	Needs to be returned for repair, please contact the sales staff or after-sales staff to send it back
	Poor wiring connection	Check whether the copper wire is full at the connection , re-plug the connector
Abnormal output value or value jumping	Interference	Check whether the two ends of the connecting cable are connected and whether the cable impedance is less than a few hundred $\Omega$ . Replace the channel test, install a power filter/isolator if necessary, replace the extension cable with a sensor-specific cable, or replace it with RHB, RHC sensors
	Magnet mismatch or damage	Check whether the magnet in the cylinder is of another brand, whether the position of the built-in magnet and the gasket is correct, whether the magnet has fallen off, etc. Externally mounted sensors check for sliding magnets off track
	Wrong selection of mounting clamp	Use mounting clamp with insulation washer (for profile structure)
	Incorrect controller parameters	Check code system, baud , monostable time, etc. If necessary, contact after-sales technicians
	Sensor damage	Check the appearance to determine whether there is damage. If damaged, needs to be returned for repair, please contact the sales staff or after-sales staff to send it back; If there is no abnormality in the appearance and no abnormality is found after the above inspection, please contact the after-sales staff for solution



## CAN

### Fault

### Reason

### Checking method

RH.RP.  
RF

Green LED is on, red LED is flashing	Magnet out of stroke length	Check the magnet, you need to move the magnet placed in the stroke test again, observe whether the light becomes green light, red light off
Red and green LED keep on	Magnet not detected	Please check whether the Magnet ring is assembled correctly
Green LED is on, red LED is off, no data	Wiring/program parameter setting error, etc	Check whether the wiring sequence is correct, whether the EDS file is correctly installed, whether the end resistance is connected, whether the baud is correctly set, whether the resistance value between CAN-H and CAN-L signal wire is about 27k $\Omega$ –50k $\Omega$ , whether there is current between the power supply and GND, whether the communication mode is asynchronous/synchronous, whether there is a start-up node instruction sent, please contact the technical or after-sales staff after the above inspection
LEDs are off	power supply/sensor failure	Check whether the power supply, whether the sensor is damaged, and return to the factory for maintenance, please contact the sales staff or after-sales staff to send it back

## Profinet

RH.RP

The green LED is on, and the data display is -1 or 0	Sensor communicating, cannot detect the magnet	The sensor output is normal, please check whether the magnet is assembled correctly and whether the measuring rod is damaged
The green LED is on, and the data display is 0x7fffffff (hexadecimal)	Sensor communicating, cannot detect magnet	The sensor output is normal, please check whether the Magnet ring is assembled correctly and whether the measuring rod is damaged
The green LED flashing and the red LED is on	Sensor internal fault	Sensor needs to be returned for repair, please contact the sales staff or after-sales staff to send it back
LEDs are off	Abnormal power supply/sensor failure	Check whether the power supply, whether the sensor is damaged, and return to the factory for maintenance, please contact the sales staff or after-sales staff to send it back
The green LED is on and the red LED is flashing	Communication failure	Check whether the GSD file matches or is correctly installed, whether the sensor name matches the configuration, modify the sensor name to simple characters such as A/a if necessary, and then configuration test

## Start-Stop

RH.RP

Green LED is on, red LED is flashing, no data	The sensor has no interrogation signal	Check whether the connection is correct, whether the controller send the start signal, and whether the hardware such as the controller module is normal
LEDs are on	Magnet or sensor failure	Check whether the magnet is assembled normally. Use frequency mode of an oscilloscope and multimeter to measure whether the waveform of start/stop signal line has amplitude or frequency value. After confirming that there is no amplitude or frequency, it must be returned to the factory for maintenance, please contact the sales staff or after-sales staff to send it back

## Profibus-DP

RH.RP

Green LED flashing, no data	Communication failure, configuration setting error, etc.	Check the communication cable connection, whether the address set in the configuration is consistent with the sensor model label, and whether the sensor address jumps (TEC address programmer is required to read the actual sensor address)
Green LED is on, no data	Abnormal configuration setting/ wrong number of magnets, etc.	Check state configuration, bus wiring, magnet number, etc.
LEDs are off	Power/Sensor Failure	Check whether the power supply is normal, whether the sensor is damaged, and return to the factory for maintenance, please contact the sales staff or after-sales staff to send it back

## Ether-CAT

RH.RP

The green LED flashing and the red LED is on	Magnet not detected/incorrect number of magnets	Check whether the magnet is assembled correctly; When there are multiple magnetic rings, check whether the actual number of magnets matches the number of set parameters
--	---	--



# Industrial Application



**Metallurgical industry**



**Port machinery**



**Hydraulic machinery**




**Wind power industry**



**Injection molding machinery**



**Vulcanizing machinery**



**Die casting machinery**



**Vertical mill machinery**



**Construction machinery**



**Papermaking machinery**



**Liquid level tank**



**Forming machinery**

## Country list

AF - Afghanistan 阿富汗	CV - Cape Verde 佛得角
AL - Albania 阿尔巴尼亚	KY - Cayman Islands 开曼群岛
DZ - Algeria 阿尔及利亚	CF - Central African Republic 中非
AS - American Samoa 东萨摩亚	TD - Chad 乍得
AD - Andorra 安道尔	CL - Chile 智利
AO - Angola 安哥拉	CN - China 中国
Av - Anguilla 安圭拉岛	CX - Christmas Island 圣诞岛
AQ - Antarctica 南极洲	CC - Cocos (Keeling) Islands 可可斯群岛
AG - Antigua and Barbuda 安提瓜和巴布达	CO - Colombia 哥伦比亚
AR - Argentina 阿根廷	KM - Comoros 科摩罗
AM - Armenia 亚美尼亚	CG - Congo 刚果
AA - Aruba 阿鲁巴	CD - Congo, Democratic Republic 刚果
AU - Australia 澳大利亚	CK - Cook Islands 库克群岛
AT - Austria 奥地利	CR - Costa Rica 哥斯达黎加
AZ - Azerbaijan 阿塞拜疆	CI - Cote D'Ivoire (Ivory Coast) 象牙海岸
	HR - Croatia (Hrvatska) 克罗地亚
BF - Bahamas 巴哈马	CU - Cuba 古巴
BH - Bahrain 巴林	CY - Cyprus 塞浦路斯
BB - Barbados 巴巴多斯	CZ - Czech Republic 捷克
BD - Bangladesh 孟加拉	CS - Czechoslovakia (former) 捷克斯洛伐克
BY - Belarus 白俄罗斯	
BE - Belgium 比利时	DK - Denmark 丹麦
BZ - Belize 伯里兹	DJ - Djibouti 吉布提
BJ - Benin 贝宁	DM - Dominica 多米尼加共和国
BM - Bermuda 百慕大	DO - Dominican Republic 多米尼加联邦
BS - Bahamas 巴哈马	
BT - Bhutan 不丹	TP - East Timor 东帝汶
BW - Botswana 博茨瓦纳	EC - Ecuador 厄瓜多尔
BO - Bolivia 玻利维亚	EG - Egypt 埃及
BA - Bosnia and Herzegovina 波黑	SV - El Salvador 萨尔瓦多
BV - Bouvet Island 布韦岛	GQ - Equatorial Guinea 赤道几内亚
BR - Brazil 巴西	ER - Eritrea
IO - British Indian Ocean Territory 英属印度洋领地	EE - Estonia 爱沙尼亚
BN - Brunei Darussalam 文莱布鲁萨兰	ET - Ethiopia 埃塞俄比亚
BG - Bulgaria 保加利亚	
BF - Burkina Faso 布基纳法索	FK - Falkland Islands (Malvinas) 福兰克群岛
BI - Burundi 布隆迪	FO - Faroe Islands 法罗群岛
	FJ - Fiji 斐济
KH - Cambodia (Internet) 柬埔寨	FI - Finland 芬兰
CB - Cambodia (CIA World Fact Book) 柬埔寨	FR - France 法国
CM - Cameroon 喀麦隆	FX - France, Metropolitan
CA - Canada 加拿大	GF - French Guiana 法属圭亚那
	PF - French Polynesia 法属玻里尼西亚

TF - French Southern Territories 法国南部 领地	KP - Korea (North) 朝鲜
MK - F.Y.R.O.M. (Macedonia)	KR - Korea (South) 韩国
	KW - Kuwait 科威特
	KG - Kyrgyzstan 吉尔吉斯斯坦
GA - Gabon 加蓬	
GM - Gambia 冈比亚	LA - Laos 老挝
GE - Georgia 格鲁吉亚	LV - Latvia 拉托维亚
DE - Germany 德国	LB - Lebanon 黎巴嫩
GH - Ghana 加纳	LI - Liechtenstein 列支顿士登
GI - Gibraltar 直布罗陀	LR - Liberia 利比里亚
GB - Great Britain (UK) 英国	LY - Libya 利比亚
GR - Greece 希腊	LS - Lesotho 莱索托
GL - Greenland 格陵兰岛	LT - Lithuania 立陶宛
GD - Grenada 格林纳达	LU - Luxembourg 卢森堡
GP - Guadeloupe 法属德洛普群岛	
GU - Guam 关岛	MO - Macau 中国澳门特区
GT - Guatemala 危地马拉	MG - Madagascar 马达加斯加
GN - Guinea 几内亚	MW - Malawi 马拉维
GW - Guinea-Bissau 几内亚比绍	MY - Malaysia 马来西亚
GY - Guyana 圭亚那	MV - Maldives 马尔代夫
	ML - Mali 马里
HT - Haiti 海地	MT - Malta 马耳他
HM - Heard and McDonald Islands 赫德和 麦克唐纳群岛	MH - Marshall Islands 马绍尔群岛
HN - Honduras 洪都拉斯	MQ - Martinique 法属马提尼克群岛
HK - Hong Kong 中国香港特区	MR - Mauritania 毛里塔尼亚
HU - Hungary 匈牙利	MU - Mauritius 毛里求斯
	YT - Mayotte
IS - Iceland 冰岛	MX - Mexico 墨西哥
IN - India 印度	FM - Micronesia 米克罗尼西亚
ID - Indonesia 印度尼西亚	MC - Monaco 摩纳哥
IR - Iran 伊朗	MD - Moldova 摩尔多瓦
IQ - Iraq 伊拉克	MA - Morocco 摩洛哥
IE - Ireland 爱尔兰	MN - Mongolia 蒙古
IL - Israel 以色列	MS - Montserrat 蒙塞拉特岛
IT - Italy 意大利	MZ - Mozambique 莫桑比克
	MM - Myanmar 缅甸
JM - Jamaica 牙买加	
JP - Japan 日本	NA - Namibia 纳米比亚
JO - Jordan 约旦	NR - Nauru 瑙鲁
	NP - Nepal 尼泊尔
KZ - Kazakhstan 哈萨克斯坦	NL - Netherlands 荷兰
KE - Kenya 肯尼亚	AN - Netherlands Antilles 荷属安德列斯
KI - Kiribati 基里巴斯	NT - Neutral Zone 中立区(沙特-伊拉克间)
	NC - New Caledonia 新卡里多尼亚

NZ - New Zealand (Aotearoa) 新西兰	SG - Singapore 新加坡
NI - Nicaragua 尼加拉瓜	SI - Slovenia 斯洛文尼亚
NE - Niger 尼日尔	SK - Slovak Republic 斯洛伐克
NG - Nigeria 尼日利亚	Sb - Solomon Islands 所罗门群岛
NU - Niue 纽爱	SO - Somalia 索马里
NF - Norfolk Island 诺福克岛	ZA - South Africa 南非
MP - Northern Mariana Islands 北马里亚纳群岛	ES - Spain 西班牙
NO - Norway 挪威	LK - Sri Lanka 斯里兰卡
	SH - St. Helena
OM - Oman 阿曼	PM - St. Pierre and Miquelon 圣皮艾尔和密克隆群岛
	SD - Sudan 苏丹
PK - Pakistan 巴基斯坦	SR - Suriname 苏里南
PW - Palau 帕劳	SJ - Svalbard and Jan Mayen Islands 斯瓦尔巴特和扬马延岛
PA - Panama 巴拿马	SZ - Swaziland 斯威士兰
PG - Papua New Guinea 巴布亚新几内亚	SE - Sweden 瑞典
PY - Paraguay 巴拉圭	CH - Switzerland 瑞士
PE - Peru 秘鲁	SY - Syria 叙利亚
PH - Philippines 菲律宾	
PN - Pitcairn 皮特克恩岛	TW - Taiwan 中国台湾省
PL - Poland 波兰	TJ - Tajikistan 塔吉克斯坦
PT - Portugal 葡萄牙	TZ - Tanzania 坦桑尼亚
PR - Puerto Rico 波多黎各	TH - Thailand 泰国
	TG - Togo 多哥
QA - Qatar 卡塔尔	TK - Tokelau 托克劳群岛
	TO - Tonga 汤加
RE - Reunion 法属尼留旺岛	TT - Trinidad and Tobago 特立尼达和多巴哥
RO - Romania 罗马尼亚	TN - Tunisia 突尼斯
RU - Russian Federation 俄罗斯	TR - Turkey 土耳其
RW - Rwanda 卢旺达	TM - Turkmenistan 土库曼斯坦
	TC - Turks and Caicos Islands 特克斯和凯科斯群岛
GS - S. Georgia and S. Sandwich Isls.	TV - Tuvalu 图瓦卢
KN - Saint Kitts and Nevis 圣基茨和尼维斯	
LC - Saint Lucia 圣卢西亚	UG - Uganda 乌干达
VC - Saint Vincent and the Grenadines 圣文森特和格陵纳丁斯	UA - Ukraine 乌克兰
WS - Samoa 西萨摩亚	AE - United Arab Emirates 阿联酋
SM - San Marino 圣马力诺	UK - United Kingdom 英国
ST - Sao Tome and Principe 圣多美和普林西比	US - United States 美国
SA - Saudi Arabia 沙特阿拉伯	UM - US Minor Outlying Islands 美国海外领地
SN - Senegal 塞内加尔	UY - Uruguay 乌拉圭
SC - Seychelles 塞舌尔	
SL - Sierra Leone 塞拉利昂	

SU - USSR (former) 前苏联  
UZ - Uzbekistan 乌兹别克斯坦

VU - Vanuatu 瓦努阿图  
VA - Vatican City State (Holy See) 梵蒂冈  
VE - Venezuela 委内瑞拉  
VN - Viet Nam 越南  
VG - Virgin Islands (British) 英属维京群岛  
VI - Virgin Islands (U.S.) 美属维京群岛

WF - Wallis and Futuna Islands 瓦利斯和福图纳群岛  
EH - Western Sahara 西撒哈拉

YE - Yemen 也门  
YU - Yugoslavia 南斯拉夫

ZM - Zambia 赞比亚  
(ZR - Zaire) - See CD Congo, Democratic Republic 扎伊尔  
ZW - Zimbabwe 津巴布韦

[www.tecsensors.com](http://www.tecsensors.com)

不求五百强 但求五百年

中国创造 · 创造中国

 **400-809-1101**

## 杭州浙达精益机电技术股份有限公司

Hangzhou Zheda Jingyi Electromechanical Technology Corporation Limited

销售热线(Sales Hotline):+86(0)571-8720 3588 / 3968

技术支持(Technical Support):+86 152 6704 5861

传 真(Fax):+86(0)571-8971 9270

邮 箱(E-mail)info.us@tecsensors.com

公司官网(Company Web): [www.tecsensors.com](http://www.tecsensors.com)

Headquarters Address (Add): Rooms 401~405, Building 18, Zhejiang Overseas High-level Talent Innovation Park, No.998 Wenyi West Road, Yuhang District, Hangzhou, Zhejiang Province

Address of Sensor Division (Add): No.8-1 Longquan Road, Cangqian Industrial Park, Yuhang District, Hangzhou City, Zhejiang Province

(New plant address: No. 4, Changsong Street, Cangqian Street, Yuhang District, Hangzhou City, Zhejiang Province)

邮 编(P.C.): 311121

Copyright © Hangzhou Zheda Jingyi Electromechanical Technology Corporation Limited 2022. All rights reserved.

Any part of this document shall not be copied in any form or manner without the prior written consent of Hangzhou Zheda Jingyi Electromechanical Technology Corporation Limited.

Mistakes or omissions in typesetting and graphics may occur and may be corrected immediately. Any changes are subject to prior notice. For more details, please visit the company website.

R-202210(C3)